

CALCULATION SUMMARY

INITIAL CONDITIONS

INIT GROUP SDSINI

INIT		DL	DP	DS
<hr/>				
T0	m	4.700	6.200	7.200
TR0	m	-0.100	0.000	0.000
HEEL0	degree	0.0	0.0	0.0
DSP0	t	6302.0	8809.7	10535.5
LCB	m	39.936	38.573	37.808
TCB	m	0.000	0.000	0.000
VCB	m	2.557	3.383	3.927
GM0	m	1.600	1.600	2.300
GM	m	1.600	1.600	2.300
KG	m	10.12	8.98	7.84
KMT	m	11.717	10.582	10.137

INDEX SUMMARY

TRIM 0

ATTAINED AND REQUIRED SUBDIVISION INDEX

Subdivision length	89.122 m
Breadth at the load line	22.000 m
Breadth at the bulkhead deck	22.000 m
Number of persons N1	0
Number of persons N2	0

Required subdivision index $R = 0.53880$

Attained subdivision index $A = 0.71873$

INIT	T m	GM m	A/R	A	A*WCOEF	WCOEF
DL	4.700	1.600	1.57	0.84476	0.16895	0.200
DP	6.200	1.600	1.34	0.71997	0.28799	0.400
DS	7.200	2.300	1.21	0.65447	0.26179	0.400

INDEX ACCORDING TO NUMBER OF ZONES

DAMAGES	W*P*V*S
1-ZONE DAMAGES	0.32836
2-ZONE DAMAGES	0.29150
3-ZONE DAMAGES	0.07741
4-ZONE DAMAGES	0.01708
5-ZONE DAMAGES	0.00438
A-INDEX TOTAL	0.71873