

# CALCULATION SUMMARY

## INITIAL CONDITIONS

### INIT GROUP SDSINI

INIT		DL	DP	DS
<hr/>				
T0	m	4.700	6.200	7.200
TR0	m	-0.100	0.000	0.000
HEEL0	degree	0.0	0.0	0.0
DSP0	t	6302.0	8809.7	10535.5
LCB	m	39.936	38.573	37.808
TCB	m	0.000	0.000	0.000
VCB	m	2.557	3.383	3.927
GM0	m	1.600	1.600	2.300
GM	m	1.600	1.600	2.300
KG	m	10.12	8.98	7.84
KMT	m	11.717	10.582	10.137

## INDEX SUMMARY

TRIM 0

### ATTAINED AND REQUIRED SUBDIVISION INDEX

Subdivision length	89.122 m
Breadth at the load line	22.000 m
Breadth at the bulkhead deck	22.000 m
Number of persons N1	0
Number of persons N2	0

Required subdivision index  $R = 0.53880$

Attained subdivision index  $A = 0.75359$

INIT	T m	GM m	A/R	A	A*WCOEF	WCOEF
DL	4.700	1.600	1.57	0.84480	0.16896	0.200
DP	6.200	1.600	1.42	0.76435	0.30574	0.400
DS	7.200	2.300	1.29	0.69724	0.27890	0.400

### INDEX ACCORDING TO NUMBER OF ZONES

DAMAGES	W*P*V*S
1-ZONE DAMAGES	0.33487
2-ZONE DAMAGES	0.32187
3-ZONE DAMAGES	0.07851
4-ZONE DAMAGES	0.01519
5-ZONE DAMAGES	0.00316
A-INDEX TOTAL	0.75359