

CTM16 instruction set

Complete instruction set definition for RTL and Archc generator



Ronan Barzic

CTM16 instruction set

Complete instruction set definition for RTL and Archc generator

Edition 0

Author

Ronan Barzic

ronan.barzic@atmel.com.com

Describe the CTM16 instruction set

Preface	ix
1. Instruction set summary	1
1.1. Instruction table	1
1.2. Condition code table	2
1.3. Instruction formats	2
1.3.1. Type I	2
1.3.1.1. Format definition	2
1.3.1.2. Specification list	3
1.3.2. Type II	3
1.3.2.1. Format definition	3
1.3.2.2. Specification list	4
1.3.3. Type III	4
1.3.3.1. Format definition	4
1.3.3.2. Specification list	5
1.3.4. Type IV	5
1.3.4.1. Format definition	5
1.3.4.2. Specification list	6
1.3.5. Type V	6
1.3.5.1. Format definition	6
1.3.5.2. Specification list	7
1.3.6. Type VI	7
1.3.6.1. Format definition	7
1.3.6.2. Specification list	8
1.3.7. Type VII	8
1.3.7.1. Format definition	8
1.3.7.2. Specification list	9
1.3.8. Type VIII	9
1.3.8.1. Format definition	9
1.3.8.2. Specification list	9
1.3.9. Type IX	10
1.3.9.1. Format definition	10
1.3.9.2. Specification list	10
2. Detailed instruction set	11
2.1. add2c	11
2.1.1. Instruction definition	11
2.1.2. Instruction implementation	11
2.1.3. Assembler implementation	11
2.1.4. Specification list	12
2.2. add2	12
2.2.1. Instruction definition	12
2.2.2. Instruction implementation	12
2.2.3. Assembler implementation	12
2.2.4. Specification list	13
2.3. add3	13
2.3.1. Instruction definition	13
2.3.2. Instruction implementation	13
2.3.3. Assembler implementation	13
2.3.4. Specification list	14
2.4. andr1	14
2.4.1. Instruction definition	14
2.4.2. Instruction implementation	14
2.4.3. Assembler implementation	14
2.4.4. Specification list	14

2.5. and	15
2.5.1. Instruction definition	15
2.5.2. Instruction implementation	15
2.5.3. Assembler implementation	15
2.5.4. Specification list	15
2.6. brpc	16
2.6.1. Instruction definition	16
2.6.2. Instruction implementation	16
2.6.3. Assembler implementation	16
2.6.4. Specification list	16
2.7. br	17
2.7.1. Instruction definition	17
2.7.2. Instruction implementation	17
2.7.3. Assembler implementation	17
2.7.4. Specification list	17
2.8. halt	18
2.8.1. Instruction definition	18
2.8.2. Instruction implementation	18
2.8.3. Assembler implementation	18
2.8.4. Specification list	19
2.9. lb	19
2.9.1. Instruction definition	19
2.9.2. Instruction implementation	19
2.9.3. Assembler implementation	19
2.9.4. Specification list	20
2.10. ldir1	20
2.10.1. Instruction definition	20
2.10.2. Instruction implementation	20
2.10.3. Assembler implementation	20
2.10.4. Specification list	21
2.11. lw	21
2.11.1. Instruction definition	21
2.11.2. Instruction implementation	21
2.11.3. Assembler implementation	21
2.11.4. Specification list	22
2.12. mfsr	22
2.12.1. Instruction definition	22
2.12.2. Instruction implementation	22
2.12.3. Assembler implementation	22
2.12.4. Specification list	23
2.13. mtsr	23
2.13.1. Instruction definition	23
2.13.2. Instruction implementation	23
2.13.3. Assembler implementation	23
2.13.4. Specification list	24
2.14. ori4	24
2.14.1. Instruction definition	24
2.14.2. Instruction implementation	24
2.14.3. Assembler implementation	24
2.14.4. Specification list	25
2.15. orr1	25
2.15.1. Instruction definition	25
2.15.2. Instruction implementation	25
2.15.3. Assembler implementation	25

2.15.4. Specification list	25
2.16. or	26
2.16.1. Instruction definition	26
2.16.2. Instruction implementation	26
2.16.3. Assembler implementation	26
2.16.4. Specification list	26
2.17. ret	27
2.17.1. Instruction definition	27
2.17.2. Instruction implementation	27
2.17.3. Assembler implementation	27
2.17.4. Specification list	28
2.18. sb	28
2.18.1. Instruction definition	28
2.18.2. Instruction implementation	28
2.18.3. Assembler implementation	28
2.18.4. Specification list	28
2.19. sext	29
2.19.1. Instruction definition	29
2.19.2. Instruction implementation	29
2.19.3. Assembler implementation	29
2.19.4. Specification list	29
2.20. slli	30
2.20.1. Instruction definition	30
2.20.2. Instruction implementation	30
2.20.3. Assembler implementation	30
2.20.4. Specification list	30
2.21. sll	31
2.21.1. Instruction definition	31
2.21.2. Instruction implementation	31
2.21.3. Assembler implementation	31
2.21.4. Specification list	31
2.22. srai	32
2.22.1. Instruction definition	32
2.22.2. Instruction implementation	32
2.22.3. Assembler implementation	32
2.22.4. Specification list	32
2.23. sra	33
2.23.1. Instruction definition	33
2.23.2. Instruction implementation	33
2.23.3. Assembler implementation	33
2.23.4. Specification list	33
2.24. srli	34
2.24.1. Instruction definition	34
2.24.2. Instruction implementation	34
2.24.3. Assembler implementation	34
2.24.4. Specification list	34
2.25. srl	35
2.25.1. Instruction definition	35
2.25.2. Instruction implementation	35
2.25.3. Assembler implementation	35
2.25.4. Specification list	35
2.26. sub2c	36
2.26.1. Instruction definition	36
2.26.2. Instruction implementation	36

2.26.3. Assembler implementation	36
2.26.4. Specification list	36
2.27. sub2	37
2.27.1. Instruction definition	37
2.27.2. Instruction implementation	37
2.27.3. Assembler implementation	37
2.27.4. Specification list	37
2.28. sub3	38
2.28.1. Instruction definition	38
2.28.2. Instruction implementation	38
2.28.3. Assembler implementation	38
2.28.4. Specification list	38
2.29. sw	39
2.29.1. Instruction definition	39
2.29.2. Instruction implementation	39
2.29.3. Assembler implementation	39
2.29.4. Specification list	39
2.30. xnorr1	40
2.30.1. Instruction definition	40
2.30.2. Instruction implementation	40
2.30.3. Assembler implementation	40
2.30.4. Specification list	40
2.31. xnor	40
2.31.1. Instruction definition	40
2.31.2. Instruction implementation	41
2.31.3. Assembler implementation	41
2.31.4. Specification list	41
2.32. xorri1	41
2.32.1. Instruction definition	41
2.32.2. Instruction implementation	42
2.32.3. Assembler implementation	42
2.32.4. Specification list	42
2.33. xor	42
2.33.1. Instruction definition	42
2.33.2. Instruction implementation	42
2.33.3. Assembler implementation	43
2.33.4. Specification list	43
3. Internal GAS Pseudo-instructions	45
3.1. zldi	45
3.1.1. Instruction definition	45
3.1.2. Specification list	45
3.2. zjump	45
3.2.1. Instruction definition	45
3.2.2. Specification list	46
4. Pseudo-instructions implemented as GAS macro	47
4.1. 32-bit arithmetic instruction	47
4.1.1. zadd32 : 32-bit addition	47
5. Processing Element detailed instruction set	49
5.1. Instruction formats	49
5.1.1. Type I	49
5.1.1.1. Format definition	49
5.1.1.2. Specification list	50

5.2. p_add	50
5.2.1. Instruction definition	50
5.2.2. Instruction implementation	50
5.2.3. Assembler implementation	51
5.2.4. Specification list	51
5.3. p_or	51
5.3.1. Instruction definition	51
5.3.2. Instruction implementation	51
5.3.3. Assembler implementation	52
5.3.4. Specification list	52
A. Revision History	53
Index	55

Preface

Instruction set summary



Note to the reader

The following tables are autogenerated...

1.1. Instruction table

Table 1.1. Instruction summary

Name	Function	Type	[15..12]	[11..8]	[7..4]	[3..0]
add2	16-bit signed addition	I	0x1	rd	rs1	uk4
add2c	16-bit addition with carry	III	0x7	rd	0x8	rs2
add3	16-bit signed addition	VII	0xc	rd	rs1	rs2
and	16-bit bitwise and	III	0x7	rd	0x0	rs2
andr1	Bitwise and with r1 and immediate value	IV	0x8	rd	0x0	uk4
br	Branch if condition, address from a register	VI	0xa	cond	rd	k4
brpc	Branch if condition, relative to pc	V	0x9	cond	k8[7..0]	k8[3..0]
halt	Halt the CPU	VIII	0xe	rd	rs1	0x3
lb	Load byte	II	0x4	rd	rs1	uk4
ldir1	Load 12-bit immediate value in upper part of r1	IX	0xf	k12[11..8]	k12[7..4]	k12[3..0]
lw	Load word	II	0x3	rd	rs1	uk4
mfsr	Move from special register	VIII	0xe	rd	rs1	0x1
mtsr	Move to special register	VIII	0xe	rd	rs1	0x0
or	16-bit bitwise or	III	0x7	rd	0x1	rs2
ori4	immediate OR with 4-bit value	I	0x0	rd	rs1	uk4
orr1	Bitwise or with r1 and immediate value	IV	0x8	rd	0x1	uk4
ret	Return from function call	VIII	0xe	rd	rs1	0x2
sb	Store byte	II	0x6	rd	rs1	uk4
sext	8-bit to 16-bit Sign extention	III	0x7	rd	0x7	rs2
sll	16-bit Shift Left, Logical	III	0x7	rd	0x6	rs2
slli	Shift Left, Logical, using immediate value	IV	0x8	rd	0x7	uk4
sra	16-bit Shift Right, arithmetic	III	0x7	rd	0x4	rs2
srai	Shift Right, Arithmetic, using immediate value	IV	0x8	rd	0x5	uk4
srl	16-bit Shift Right, Logical	III	0x7	rd	0x5	rs2

Name	Function	Type	[15..12]	[11..8]	[7..4]	[3..0]
srl	Shift Right, Logical, using immediate value	IV	0x8	rd	0x6	uk4
sub2	16-bit signed subtraction	I	0x2	rd	rs1	uk4
sub2c	16-bit subtraction with carry	III	0x7	rd	0x9	rs2
sub3	16-bit signed addition	VII	0xd	rd	rs1	rs2
sw	Store word	II	0x5	rd	rs1	uk4
xnor	16-bit bitwise negated exclusive or	III	0x7	rd	0x3	rs2
xnorr1	Bitwise xnor with r1 and immediate value	IV	0x8	rd	0x3	uk4
xor	16-bit bitwise exclusive or	III	0x7	rd	0x2	rs2
xorr1	Bitwise xor with r1 and immediate value	IV	0x8	rd	0x2	uk4

1.2. Condition code table

Table 1.2. Condition code

Name	Value	Function
al	14	Always
alal	15	Always and link
c	10	Carry set
eq	0	Equal (signed)
ge	5	Greater or equal (signed)
geu	9	Greater or equal (unsigned)
gt	4	Greater than (signed)
gtu	8	Greater than (unsigned)
le	3	Less or equal (signed)
leu	7	Less or equal (unsigned)
lt	2	Less than (signed)
ltu	6	Less than (unsigned)
neq	1	Not equal (signed)
o	11	Overflow (signed)
ou	0	Overflow (unsigned)

1.3. Instruction formats

1.3.1. Type I

1.3.1.1. Format definition

--

```

spec['useq']['inst_type']['Type_I']['format']= {
    'opcode1' : {'size' : 4,
                 'offset' : 12,
                 'decode' : True, # Field is used for decoding
                 },
    'rd'      : {'size' : 4,
                 'offset' : 8
                 },
    'rs1'     : {'size' : 4,
                 'offset' : 4
                 },
    'uk4'     : {'size' : 4,
                 'offset' : 0
                 },
}
}

# default implementation
spec['useq']['inst_type']['Type_I']['impl']= {
    'rf' : {
        'sela' : 'rd',
        'selb' : 'rs1',
        'selc' : 'rd',
    },
    'writeback' : {
        'source' : "alu",
        'dest'   : "rfc[rd]",
    },
    'pc' : {
        'next' : 'increment'
    }
}

spec['useq']['inst_type']['Type_I']['asm'] = '%reg, %reg, %exp';
spec['useq']['inst_type']['Type_I']['fields']= 'rd, rs1, uk4';
# just an helper for quick docbook generation - we could write some code to do it
automatically...
spec['useq']['inst_type']['Type_I']['docbook']= ('opcode1', 'rd', 'rs1', 'uk4');

```

1.3.1.2. Specification list

```
<src:fragref linkend="src_inst_def_format_type_i"></src:fragref>
```

1.3.2. Type II

1.3.2.1. Format definition

```

spec['useq']['inst_type']['Type_II']['format']= {
    'opcode1' : {'size' : 4,
                 'offset' : 12,
                 'decode' : True, # Field is used for decoding
                 },
}

```

```

'rd'      : {'size'   : 4,
             'offset'  : 8
           },
'rs1'     : {'size'   : 4,
             'offset'  : 4
           },
'k4'      : {'size'   : 4,
             'offset'  : 0,
             'signed' : True
           },
}

spec['useq'][['inst_type']['Type_II']]['impl'] = {
    'pc' : {
        'next' : 'increment'
    },
    'flag' : {
        'carry_in' : 0,
        'carry'   : 'keep',
    },
    'rf' : {
        'sela' : 'rs1',
        'selb' : 'rs1', # default..?
        'selc' : 'rd', # default..?
    },
}

spec['useq'][['inst_type']['Type_II']]['asm'] = '%reg, %reg, %exp';
spec['useq'][['inst_type']['Type_II']]['fields'] = 'rd, rs1, k4';

spec['useq'][['inst_type']['Type_II']]['docbook'] = ('opcode1', 'rd', 'rs1', 'uk4');

```

1.3.2.2. Specification list

```
<src:fragref linkend="src_inst_def_format_type_ii"></src:fragref>
```

1.3.3. Type III

1.3.3.1. Format definition

```

spec['useq'][['inst_type']['Type_III']]['format'] = {
    'opcode1' : {'size'   : 4,
                 'offset'  : 12,
                 'decode'  : True, # Field is used for decoding
               },
    'rd'      : {'size'   : 4,
                 'offset'  : 8
               },
    'opcode3' : {'size'   : 4,
                 'offset'  : 4,
                 'decode'  : True, # Field is used for decoding
               },
    'rs2'     : {'size'   : 4,
                 'offset'  : 0,
               }
}

```

```

        },
    }

spec['useq']['inst_type']['Type_III']['impl']= {
    'pc' : {
        'next' : 'increment'
    },
    'rf' : {
        'sela' : 'rd',
        'selb' : 'rs2',
        'selc' : 'rd',
    },
    'writeback' : {
        'source' : "alu",
        'dest' : "rfc[rd]",
    },
    'flag' : { # some type_III instructions will override that
        'carry_in' : 0,
        'carry' : 'keep',
    },
}
}

spec['useq']['inst_type']['Type_III']['asm'] = '%reg, %reg';
spec['useq']['inst_type']['Type_III']['fields']= 'rd, rs2';

spec['useq']['inst_type']['Type_III']['docbook']= ('opcodel','rd', 'opcode3', 'rs2');

```

1.3.3.2. Specification list

```
<src:fragref linkend="src_inst_def_format_type_iii"></src:fragref>
```

1.3.4. Type IV

1.3.4.1. Format definition

```

spec['useq']['inst_type']['Type_IV']['format']= {
    'opcodel' : {'size' : 4,
                 'offset' : 12,
                 'decode' : True, # Field is used for decoding
    },
    'rd' : {'size' : 4,
            'offset' : 8
    },
    'opcode3' : {'size' : 4,
                 'offset' : 4,
                 'decode' : True, # Field is used for decoding
    },
    'uk4' : {'size' : 4,
              'offset' : 0,
    },
}
}

spec['useq']['inst_type']['Type_IV']['impl']= {

```

```

'rf' : {
    'sela' : 'rd',
    'selb' : 'rl', # yes , we force rl usage here
    'selc' : 'rd',
},
'pc' : {
    'next' : 'increment'
},
'writeback' : {
    'source' : "alu",
    'dest' : "rfc[rd]",
},
'flag' : { # some type_IV instructions will override that
    'carry_in' : 0,
    'carry' : 'keep',
},
}

spec['useq'][['inst_type']['Type_IV']['asm']] = '%reg, %exp';

spec['useq'][['inst_type']['Type_IV']['fields']] = 'rd, uk4';

spec['useq'][['inst_type']['Type_IV']['docbook']] = ('opcode1','rd', 'opcode3', 'uk4');

```

1.3.4.2. Specification list

```
<src:fragref linkend="src_inst_def_format_type_iv"></src:fragref>
```

1.3.5. Type V

1.3.5.1. Format definition

```

spec['useq'][['inst_type']['Type_V']['format']] = {
    'opcode1' : {'size' : 4,
                 'offset' : 12,
                 'decode' : True, # Field is used for decoding
                },
    'cond' : {'size' : 4,
              'offset' : 8,
              'decode' : True, # Field is used for decoding
             },
    'k8' : {'size' : 8,
            'offset' : 0,
            'signed' : True
           },
}

spec['useq'][['inst_type']['Type_V']['impl']] = {
    'rf' : {
        'sela' : 'rd',
        'selb' : 'rs1', # default - we don't use the RF
        'selc' : 'rs2',
    },
}

```

```

    'writeback' : {
        'source' : "alu",
        'dest' : "pc",
    },
    'flag' : { # some type_IV instructions will override that
        'carry_in' : 0,
        'carry' : 'keep',
    },
},
}

spec['useq']['inst_type']['Type_V']['asm'] = '%exp';
spec['useq']['inst_type']['Type_V']['fields'] = 'k8';

spec['useq']['inst_type']['Type_V']['docbook'] = ('opcodel', 'cond', 'k8[7..0]', 'k8[3..0]');

```

1.3.5.2. Specification list

```
<src:fragref linkend="src_inst_def_format_type_v"></src:fragref>
```

1.3.6. Type VI

1.3.6.1. Format definition

```

spec['useq']['inst_type']['Type_VI']['format'] = {
    'opcodel' : {'size' : 4,
                 'offset' : 12,
                 'decode' : True, # Field is used for decoding
    },
    'cond' : {'size' : 4,
              'offset' : 8,
              'decode' : True, # Field is used for decoding
    },
    'rd' : {'size' : 4,
            'offset' : 4,
    },
    'uk4' : {'size' : 4,
              'offset' : 0
    },
}
}

spec['useq']['inst_type']['Type_VI']['impl'] = {
    'rf' : {
        'sela' : 'r0',
        'selb' : 'rs1',
        'selc' : 'r0',
    },
    'writeback' : {
        'source' : "alu",
        'dest' : "pc",
    },
    'flag' : { # some type_IV instructions will override that
        'carry_in' : 0,
        'carry' : 'keep',
    },
}

```

```

    },
}

spec['useq'][['inst_type'][['Type_VI']]][['asm']] = '%reg,%exp';
spec['useq'][['inst_type'][['Type_VI']]][['fields']] = 'rd,uk4';

spec['useq'][['inst_type'][['Type_VI']]][['docbook']] = ('opcode1','cond', 'rd','k4');

```

1.3.6.2. Specification list

```
<src:fragref linkend="src_inst_def_format_type_vi"></src:fragref>
```

1.3.7. Type VII

1.3.7.1. Format definition

```

spec['useq'][['inst_type'][['Type_VII']]][['format']] = {

    'opcode1' : {'size' : 4,
                 'offset' : 12,
                 'decode' : True, # Field is used for decoding
                 },
    'rd'      : {'size' : 4,
                 'offset' : 8
                 },
    'rs1'    : {'size' : 4,
                 'offset' : 4,
                 },
    'rs2'    : {'size' : 4,
                 'offset' : 0
                 },
}

spec['useq'][['inst_type'][['Type_VII']]][['impl']] = {
    'rf' : {
        'selA' : 'rs1',
        'selB' : 'rs2',
        'selC' : 'rd',
        },
    'pc' : {
        'next' : 'increment',
        },
    'rf' : {
        'selA' : 'rs1',
        'selB' : 'rs2',
        'selC' : 'rd',
        },
    'writeback' : {
        'source' : "alu",
        'dest'   : "rfc[rd]",
        },
}

```

```
spec['useq']['inst_type']['Type_VII']['asm'] = '%reg,%reg,%reg';
spec['useq']['inst_type']['Type_VII']['fields']= 'rd,rsl,rs2';
spec['useq']['inst_type']['Type_VII']['docbook']= ('opcode1','rd', 'rsl','rs2');
```

1.3.7.2. Specification list

```
<src:fragref linkend="src_inst_def_format_type_vii">></src:fragref>
```

1.3.8. Type VIII

1.3.8.1. Format definition

```
spec['useq']['inst_type']['Type_VIII']['format']= {

    'opcode1' : {'size' : 4,
                 'offset' : 12,
                 'decode' : True, # Field is used for decoding
                 },
    'rd'      : {'size' : 4,
                 'offset' : 8
                 },
    'rsl'    : {'size' : 4,
                 'offset' : 4,
                 },
    'opcode4' : {'size' : 4,
                 'offset' : 0,
                 'decode' : True, # Field is used for decoding
                 },
}

spec['useq']['inst_type']['Type_VIII']['impl']= {
    'pc' : {
        'next' : 'increment',
    },
}

# custom asm per instruction is probably needed
spec['useq']['inst_type']['Type_VIII']['asm'] = '%reg,%reg';
spec['useq']['inst_type']['Type_VIII']['fields']= 'rd,rsl';

spec['useq']['inst_type']['Type_VIII']['docbook']= ('opcode1','rd', 'rsl','opcode4');
```

1.3.8.2. Specification list

```
<src:fragref linkend="src_inst_def_format_type_viii">></src:fragref>
```

1.3.9. Type IX

1.3.9.1. Format definition

```
# for the ldirl instruction
spec['useq']['inst_type']['Type_IX']['format']= {

    'opcode1' : {'size' : 4,
                 'offset' : 12,
                 'decode' : True, # Field is used for decoding
                 },
    'k12'     : {'size' : 12,
                 'offset' : 0,
                 },
}

spec['useq']['inst_type']['Type_IX']['impl']= {
    'pc' : {
        'next' : 'increment',
        },
}

# custom asm per instruction is probably needed
spec['useq']['inst_type']['Type_IX']['asm'] = '%exp';
spec['useq']['inst_type']['Type_IX']['fields']= 'k12';

spec['useq']['inst_type']['Type_IX']['docbook']= ('opcode1','k12[11..8]',
    'k12[7..4]','k12[3..0]');
```

1.3.9.2. Specification list

```
<src:fragref linkend="src_inst_def_format_type_ix"></src:fragref>
```

Detailed instruction set



Note to the reader

The following sections contain description of all instructions used by the µSequencer. Behaviour of each instruction is described as a set of properties (expressed as a Python dictionary) that are used to generate Verilog code, Assembler and ArchC configuration code (for binutils tools like GAS...)

2.1. add2c

2.1.1. Instruction definition

```
spec['useq']['inst']['add2c'] = {
    'fullname' : 'add2c',
    'Description' : '16-bit addition with carry',
    'opcode1' : 7,
    'opcode3' : 8,
    'type' : 'Type_III',
}
```

2.1.2. Instruction implementation

```
spec['useq']['inst']['add2c']['impl'] = {

    'alu' : {
        'op' : 'add',
        'sourcea' : 'rfa[rd]',
        'sourceb' : 'rbf[rs2]',
    },

    'flag' : {
        'carry_in' : 'carry',
        'carry' : 'update',
    }
}
```

2.1.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.1.4. Specification list

```
<src:fragref linkend="src_inst_def_add2c"></src:fragref>
<src:fragref linkend="src_inst_impl_add2c"></src:fragref>
<src:fragref linkend="src_inst_asm_add2c"></src:fragref>
```

2.2. add2

2.2.1. Instruction definition

```
spec['useq']['inst']['add2'] = {
    'fullname' : 'add2',
    'Description' : '16-bit signed addition',
    'opcodel' : 1,
    'type' : 'Type_I',
}
```

2.2.2. Instruction implementation

```
spec['useq']['inst']['add2']['impl'] = {

    'alu' : {
        'op' : 'add',
        'sourcea' : 'rfa[rd]',
        'sourceb' : 'rfb[rsl]_or_uk4',
    },
    'flag' : {
        'carry_in' : 0,
        'carry' : 'update',
    }
}

#spec['useq']['inst']['add']['asm'] = {
#    'main' : "add(rf[rs1],rf[rs2])",
#    'variant1' : "add(rf[rs1],rf[rs2])",
#}
```

2.2.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.2.4. Specification list

```
<src:fragref linkend="src_inst_def_add2"></src:fragref>
<src:fragref linkend="src_inst_impl_add2"></src:fragref>
<src:fragref linkend="src_inst_asm_add2"></src:fragref>
```

2.3. add3

2.3.1. Instruction definition

```
spec['useq']['inst']['add3'] = {
    'fullname' : 'add3',
    'Description' : '16-bit signed addition',
    'opcode1' : 0xC,
    'type' : 'Type_VII',
}
```

2.3.2. Instruction implementation

```
spec['useq']['inst']['add3']['impl'] = {

    'alu' : {
        'op' : 'add',
        'sourcea' : 'rfa[rs1]',
        'sourceb' : 'rbf[rs2]',
    },
    'flag' : { # some type_IV instructions will override that
        'carry_in' : 0,
        'carry' : 'update',
    },
}
```

2.3.3. Assembler implementation

```
# Special variant to support expression instead of "pure" register name
# - To be used in gas macro
spec['useq']['inst']['add3']['asm'] = {
    'main' : '\\"add3 %reg,%reg,%reg\\' + ',rd,rs1,rs2',
    'variant1' : '\\"add3 %exp,%exp,%exp\\' + ',rd,rs1,rs2',
}
```

2.3.4. Specification list

```
<src:fragref linkend="src_inst_def_add3"></src:fragref>
<src:fragref linkend="src_inst_impl_add3"></src:fragref>
<src:fragref linkend="src_inst_asm_add3"></src:fragref>
```

2.4. andr1

2.4.1. Instruction definition

```
spec['useq']['inst']['andr1'] = {
    'fullname' : 'andr1',
    'Description' : 'Bitwise and with r1 and immediate value',
    'opcode1' : 0x8,
    'opcode3' : 0x0,
    'type' : 'Type_IV',
}
```

2.4.2. Instruction implementation

```
spec['useq']['inst']['andr1']['impl'] = {
    'alu' : {
        'op' : 'and',
        'sourcea' : 'rfa[rd]',
        'sourceb' : 'rfb[r1]_or_uk4',
    },
}
```

2.4.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.4.4. Specification list

```
<src:fragref linkend="src_inst_def_andr1"></src:fragref>
<src:fragref linkend="src_inst_impl_andr1"></src:fragref>
<src:fragref linkend="src_inst_asm_andr1"></src:fragref>
```

2.5. and

2.5.1. Instruction definition

```
spec['useq']['inst']['and'] = {
    'fullname' : 'and',
    'Description' : '16-bit bitwise and',
    'opcode1' : 7,
    'opcode3' : 0,
    'type' : 'Type_III',
}
```

2.5.2. Instruction implementation

```
spec['useq']['inst']['and']['impl'] = {
    'alu' : {
        'op' : 'and',
        'sourcea' : 'rfa[rd]',
        'sourceb' : 'rbf[rs2]',
    },
    'flag' : {
        'carry_in' : 0,
        'carry' : 'keep',
    }
}
```

2.5.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.5.4. Specification list

```
<src:fragref linkend="src_inst_def_and"></src:fragref>
<src:fragref linkend="src_inst_impl_and"></src:fragref>
<src:fragref linkend="src_inst_asm_and"></src:fragref>
```

2.6. brpc

2.6.1. Instruction definition

```
spec['useq']['inst']['brpc'] = {
    'fullname' : 'brpc',
    'Description' : 'Branch if condition, relative to pc',
    'opcode1' : 0x9,
    'type' : 'Type_V',
}
```

2.6.2. Instruction implementation

```
spec['useq']['inst']['brpc']['impl'] = {
    'alu' : {
        'op' : 'add',
        'sourcea' : 'npc',
        'sourceb' : 'k8',
    },
    'pc' : {
        'next' : 'cond_load_from_alu'
    },
    'writeback' : {
        'source' : "alu",
        'dest' : "cond_link_reg", # if condition is F, then this is an unconditionnal
branch, with link
    },
}
```

2.6.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.6.4. Specification list

```
<src:fragref linkend="src_inst_def_brpc"></src:fragref>
<src:fragref linkend="src_inst_impl_brpc"></src:fragref>
```

```
<src:fragref linkend="src_inst_asm_brpc"></src:fragref>
```

2.7. br

2.7.1. Instruction definition

```
spec['useq']['inst']['br'] = {
    'fullname' : 'br',
    'Description' : 'Branch if condition, address from a register',
    'opcode1' : 0xA,
    'type' : 'Type_VI',
}
```

2.7.2. Instruction implementation

```
spec['useq']['inst']['br']['impl'] = {
    'alu' : {
        'op' : 'add',
        'sourcea' : 'rfa[r0]', # set in the instruction format definition
        'sourceb' : 'rbf[rs1]_or_uk4',
    },
    'pc' : {
        'next' : 'cond_load_from_alu'
    },
    'writeback' : {
        'source' : "alu",
        'dest' : "cond_link_reg", # if condition is F, then this is an unconditional branch, with link
    },
}
```

2.7.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.7.4. Specification list

```
<src:fragref linkend="src_inst_def_br"></src:fragref>
<src:fragref linkend="src_inst_impl_br"></src:fragref>
<src:fragref linkend="src_inst_asm_br"></src:fragref>
```

2.8. halt

2.8.1. Instruction definition

```
spec['useq'][['inst']]['halt'] = {
    'fullname' : 'halt',
    'Description' : 'Halt the CPU',
    'opcode1' : 0xE,
    'opcode4' : 0x3,
    'type' : 'Type_VIII',
}
```

2.8.2. Instruction implementation

```
spec['useq'][['inst']]['halt'][['impl']] = {
    'rf' : {
        'selA' : 'r0', # Don't care
        'selB' : 'rs1', # Don't care
        'selC' : 'r0', # Don't care
    },
    'alu' : {
        'op' : 'add',
        'sourceA' : 'rfa[r0]', # should be 0
        'sourceB' : 'rbf[rs1]',
    },
    'writeback' : {
        'source' : 'alu',
        'dest' : 'rfc', # r0
    },
    'flag' : {
        'carry_in' : 0,
        'carry' : 'keep',
    },
    'pc' : {
        'next' : 'increment'
    },
    'flow' : {
        'halt' : 'yes' # we stop...
    },
}
```

2.8.3. Assembler implementation

```
spec['useq'][['inst']]['halt'][['asm']] = {
```

```

    'main'          : '\\"halt %exp\\' +' ,rd',
}

```

2.8.4. Specification list

```

<src:fragref linkend="src_inst_def_halt"></src:fragref>
<src:fragref linkend="src_inst_impl_halt"></src:fragref>
<src:fragref linkend="src_inst_asm_halt"></src:fragref>

```

2.9. Ib

2.9.1. Instruction definition

```

spec['useq']['inst']['lb'] = {
    'fullname' : 'lb',
    'Description' : 'Load byte',
    'opcode1' : 4,
    'type' : 'Type_II',
}

```

2.9.2. Instruction implementation

```

spec['useq']['inst']['lb']['impl'] = {

    'alu' : {
        'op' : 'add',
        'sourcea' : 'rfa[rs1]',
        'sourceb' : 'k4',
    },

    'writeback' : {
        'source' : "mem8",
        'dest' : "rfc[rd]",
    },
}

```

2.9.3. Assembler implementation

```

# ASM :
# No special implementation - following default for instruction type

```

2.9.4. Specification list

```
<src:fragref linkend="src_inst_def_lb"></src:fragref>
<src:fragref linkend="src_inst_impl_lb"></src:fragref>
<src:fragref linkend="src_inst_asm_lb"></src:fragref>
```

2.10. ldir1

2.10.1. Instruction definition

```
spec['useq']['inst']['ldir1'] = {
    'fullname' : 'ldir1',
    'Description' : 'Load 12-bit immediate value in upper part of r1',
    'opcode1' : 0xF,
    'type' : 'Type_IX',
}
```

2.10.2. Instruction implementation

```
spec['useq']['inst']['ldir1']['impl'] = {
    'rf' : {
        'selA' : 'r0', # read a 0
        'selB' : 'rs2', # dont care
        'selC' : 'r1', # we force the write in r1
    },
    'alu' : {
        'op' : 'add',
        'sourceA' : 'rfa[r0]', # should be 0
        'sourceB' : 'k12',
    },
    'writeback' : {
        'source' : 'alu',
        'dest' : 'rfc[rd]',
    },
    'flag' : {
        'carry_in' : 0,
        'carry' : 'keep',
    },
}
```

2.10.3. Assembler implementation

```
# ASM :
```

```
# No special implementation - following default for instruction type
```

2.10.4. Specification list

```
<src:fragref linkend="src_inst_def_ldir1"></src:fragref>
<src:fragref linkend="src_inst_impl_ldir1"></src:fragref>
<src:fragref linkend="src_inst_asm_ldir1"></src:fragref>
```

2.11. lw

2.11.1. Instruction definition

```
spec['useq']['inst']['lw'] = {
    'fullname' : 'lw',
    'Description' : 'Load word',
    'opcode1' : 3,
    'type' : 'Type_II',
}
```

2.11.2. Instruction implementation

```
spec['useq']['inst']['lw']['impl'] = {
    'alu' : {
        'op' : 'add',
        'sourcea' : 'rfa[rs1]',
        'sourceb' : 'k4',
    },
    'writeback' : {
        'source' : "mem16",
        'dest' : "rfc[rd]",
    },
}
```

2.11.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.11.4. Specification list

```
<src:fragref linkend="src_inst_def_lw"></src:fragref>
<src:fragref linkend="src_inst_impl_lw"></src:fragref>
<src:fragref linkend="src_inst_asm_lw"></src:fragref>
```

2.12. mfsr

2.12.1. Instruction definition

```
spec['useq']['inst']['mfsr'] = {
    'fullname' : 'mfsr',
    'Description' : 'Move from special register',
    'opcode1' : 0xE,
    'opcode4' : 0x1,
    'type' : 'Type_VIII',
}
```

2.12.2. Instruction implementation

```
spec['useq']['inst']['mfsr']['impl'] = {
    'rf' : {
        'sela' : 'r0', # Force a zero
        'selb' : 'rs1', # # don't care
        'selc' : 'rd', #
    },
    'alu' : {
        'op' : 'add',
        'sourcea' : 'rfa[r0]', # should be 0
        'sourceb' : 'sr[rs1]',
    },
    'writeback' : {
        'source' : 'alu',
        'dest' : 'rfc[rd]',
    },
    'flag' : {
        'carry_in' : 0,
        'carry' : 'keep',
    },
}
```

2.12.3. Assembler implementation

```
spec['useq']['inst']['mfsr']['asm'] = {
    'main' : '"mfsr %reg,%sreg"' + ',rd,rs1',
}
```

2.12.4. Specification list

```
<src:fragref linkend="src_inst_def_mfsr"></src:fragref>
<src:fragref linkend="src_inst_impl_mfsr"></src:fragref>
<src:fragref linkend="src_inst_asm_mfsr"></src:fragref>
```

2.13. mtsr

2.13.1. Instruction definition

```
spec['useq']['inst']['mtsr'] = {
    'fullname' : 'mtsr',
    'Description' : 'Move to special register',
    'opcode1' : 0xE,
    'opcode4' : 0x0,
    'type' : 'Type_VIII',
}
```

2.13.2. Instruction implementation

```
spec['useq']['inst']['mtsr']['impl'] = {
    'rf' : {
        'sela' : 'r0', # Force a zero
        'selb' : 'rs1', # data source
        'selc' : 'rd', # don't care
    },
    'alu' : {
        'op' : 'add',
        'sourcea' : 'rfa[r0]', # should be 0
        'sourceb' : 'rb[rs1]',
    },
    'writeback' : {
        'source' : 'alu',
        'dest' : 'sr[rd]',
    },
    'flag' : {
        'carry_in' : 0,
        'carry' : 'keep',
    },
}
```

2.13.3. Assembler implementation

```
spec['useq']['inst']['mts'][['asm']] = {
    'main' : '\"mts %sreg,%reg\" '+' ,rd,rs1',
}
```

2.13.4. Specification list

```
<src:fragref linkend="src_inst_def_mtsr"></src:fragref>
<src:fragref linkend="src_inst_impl_mtsr"></src:fragref>
<src:fragref linkend="src_inst_asm_mtsr"></src:fragref>
```

2.14. ori4

2.14.1. Instruction definition

```
spec['useq']['inst']['ori4'] = {
    'fullname' : 'ori4',
    'Description' : 'immediate OR with 4-bit value',
    'opcode1' : 0,
    'type' : 'Type_I',
}
```

2.14.2. Instruction implementation

```
spec['useq']['inst']['ori4']['impl'] = {

    'rf' : {
        'selA' : 'r0', # yes, we just want to "move" data
        'selB' : 'rs1',
        'selC' : 'rd',
    },
    'alu' : {
        'op' : 'or',
        'sourceA' : 'rfa[0]',
        'sourceB' : 'rb[rs1]_or_uk4',
    },
    'flag' : {
        'carry_in' : 0,
        'carry' : 'keep',
    }
}
```

2.14.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.14.4. Specification list

```
<src:fragref linkend="src_inst_def_ori4"></src:fragref>
<src:fragref linkend="src_inst_impl_ori4"></src:fragref>
<src:fragref linkend="src_inst_asm_ori4"></src:fragref>
```

2.15. orr1

2.15.1. Instruction definition

```
spec['useq']['inst']['orr1'] = {
    'fullname' : 'orr1',
    'Description' : 'Bitwise or with r1 and immediate value',
    'opcode1' : 0x8,
    'opcode3' : 0x1,
    'type' : 'Type_IV',
}
```

2.15.2. Instruction implementation

```
spec['useq']['inst']['orr1']['impl'] = {
    'alu' : {
        'op' : 'or',
        'sourcea' : 'rfa[rd]',
        'sourceb' : 'rbf[r1]_or_uk4',
    },
}
```

2.15.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.15.4. Specification list

```
<src:fragref linkend="src_inst_def_or1"></src:fragref>
<src:fragref linkend="src_inst_impl_or1"></src:fragref>
<src:fragref linkend="src_inst_asm_or1"></src:fragref>
```

2.16. or

2.16.1. Instruction definition

```
spec['useq']['inst']['or'] = {
    'fullname' : 'or',
    'Description' : '16-bit bitwise or',
    'opcode1' : 7,
    'opcode3' : 1,
    'type' : 'Type_III',
}
```

2.16.2. Instruction implementation

```
spec['useq']['inst']['or']['impl'] = {
    'alu' : {
        'op' : 'or',
        'sourcea' : 'rfa[rd]',
        'sourceb' : 'rbf[rs2]',
    },
    'flag' : {
        'carry_in' : 0,
        'carry' : 'keep',
    }
}
```

2.16.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.16.4. Specification list

```
<src:fragref linkend="src_inst_def_or"></src:fragref>
<src:fragref linkend="src_inst_impl_or"></src:fragref>
<src:fragref linkend="src_inst_asm_or"></src:fragref>
```

2.17. ret

2.17.1. Instruction definition

```
spec['useq']['inst']['ret'] = {
    'fullname' : 'ret',
    'Description' : 'Return from function call',
    'opcode1' : 0xE,
    'opcode4' : 0x2,
    'type' : 'Type_VIII',
}
```

2.17.2. Instruction implementation

```
spec['useq']['inst']['ret']['impl'] = {
    'rf' : {
        'sela' : 'r0', # Force a zero
        'selb' : 'r14', # Link register
        'selc' : 'rd', # Don't care
    },
    'alu' : {
        'op' : 'add',
        'sourcea' : 'rfa[r0]', # should be 0
        'sourceb' : 'rbf[r14]',
    },
    'writeback' : {
        'source' : 'alu',
        'dest' : 'pc',
    },
    'flag' : {
        'carry_in' : 0,
        'carry' : 'keep',
    },
    'pc' : {
        'next' : 'from_alu'
    },
}
```

2.17.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.17.4. Specification list

```
<src:fragref linkend="src_inst_def_ret"></src:fragref>
<src:fragref linkend="src_inst_impl_ret"></src:fragref>
<src:fragref linkend="src_inst_asm_ret"></src:fragref>
```

2.18. sb

2.18.1. Instruction definition

```
spec['useq']['inst']['sb'] = {
    'fullname' : 'sb',
    'Description' : 'Store byte',
    'opcode1' : 6,
    'type' : 'Type_II',
}
```

2.18.2. Instruction implementation

```
spec['useq']['inst']['sb']['impl'] = {

    'alu' : {
        'op' : 'add',
        'sourcea' : 'rfa[rsl]',
        'sourceb' : 'k4',
    },

    'writeback' : {
        'source' : "rfb[rd]",
        'dest' : "mem8",
    },
}
```

2.18.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.18.4. Specification list

```
<src:fragref linkend="src_inst_def_sb"></src:fragref>
<src:fragref linkend="src_inst_impl_sb"></src:fragref>
<src:fragref linkend="src_inst_asm_sb"></src:fragref>
```

2.19. sext

2.19.1. Instruction definition

```
spec['useq']['inst']['sext'] = {
    'fullname' : 'sext',
    'Description' : '8-bit to 16-bit Sign extention',
    'opcode1' : 7,
    'opcode3' : 7,
    'type' : 'Type_III',
}
```

2.19.2. Instruction implementation

```
spec['useq']['inst']['sext']['impl'] = {
    'alu' : {
        'op' : 'sext',
        'sourcea' : 'rfa[rd]',
        'sourceb' : 'rbf[rs2]',
    },
    'flag' : {
        'carry_in' : 0,
        'carry' : 'keep',
    }
}
```

2.19.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.19.4. Specification list

```
<src:fragref linkend="src_inst_def_sext"></src:fragref>
<src:fragref linkend="src_inst_impl_sext"></src:fragref>
<src:fragref linkend="src_inst_asm_sext"></src:fragref>
```

2.20. slli

2.20.1. Instruction definition

```
spec['useq']['inst']['slli'] = {
    'fullname' : 'slli',
    'Description' : 'Shift Left, Logical, using immediate value',
    'opcode1' : 0x8,
    'opcode3' : 0x7,
    'type' : 'Type_IV',
}
```

2.20.2. Instruction implementation

```
spec['useq']['inst']['slli']['impl'] = {
    'alu' : {
        'op' : 'sll',
        'sourcea' : 'rfa[rd]',
        'sourceb' : 'uk4', # R1 not used
    },
    'writeback' : {
        'source' : "alu",
        'dest' : "rfc[rd]",
    },
}
```

2.20.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.20.4. Specification list

```
<src:fragref linkend="src_inst_def_slli"></src:fragref>
<src:fragref linkend="src_inst_impl_slli"></src:fragref>
<src:fragref linkend="src_inst_asm_slli"></src:fragref>
```

2.21. sll

2.21.1. Instruction definition

```
spec['useq']['inst']['sll'] = {
    'fullname' : 'sll',
    'Description' : '16-bit Shift Left, Logical ',
    'opcode1' : 7,
    'opcode3' : 6,
    'type' : 'Type_III',
}
```

2.21.2. Instruction implementation

```
spec['useq']['inst']['sll']['impl'] = {
    'alu' : {
        'op' : 'sll',
        'sourcea' : 'rfa[rd]',
        'sourceb' : 'rbf[rs2]',
    },
    'flag' : {
        'carry_in' : 0,
        'carry' : 'keep',
    }
}
```

2.21.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.21.4. Specification list

```
<src:fragref linkend="src_inst_def_sll"></src:fragref>
<src:fragref linkend="src_inst_impl_sll"></src:fragref>
<src:fragref linkend="src_inst_asm_sll"></src:fragref>
```

2.22. srai

2.22.1. Instruction definition

```
spec['useq']['inst']['srai'] = {
    'fullname' : 'srai',
    'Description' : 'Shift Right, Arithmetic, using immediate value',
    'opcode1' : 0x8,
    'opcode3' : 0x5,
    'type' : 'Type_IV',
}
```

2.22.2. Instruction implementation

```
spec['useq']['inst']['srai']['impl'] = {
    'alu' : {
        'op' : 'sra',
        'sourcea' : 'rfa[rd]',
        'sourceb' : 'uk4', # R1 not used
    },
    'writeback' : {
        'source' : "alu",
        'dest' : "rfc[rd]",
    },
}
```

2.22.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.22.4. Specification list

```
<src:fragref linkend="src_inst_def_srai"></src:fragref>
<src:fragref linkend="src_inst_impl_srai"></src:fragref>
<src:fragref linkend="src_inst_asm_srai"></src:fragref>
```

2.23. sra

2.23.1. Instruction definition

```
spec['useq']['inst']['sra'] = {
    'fullname' : 'sra',
    'Description' : '16-bit Shift Right, arithmetic',
    'opcode1' : 7,
    'opcode3' : 4,
    'type' : 'Type_III',
}
```

2.23.2. Instruction implementation

```
spec['useq']['inst']['sra']['impl'] = {

    'alu' : {
        'op' : 'sra',
        'sourcea' : 'rfa[rd]',
        'sourceb' : 'rbf[rs2]',
    },

    'flag' : {
        'carry_in' : 0,
        'carry' : 'keep',
    }
}
```

2.23.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.23.4. Specification list

```
<src:fragref linkend="src_inst_def_sra"></src:fragref>
<src:fragref linkend="src_inst_impl_sra"></src:fragref>
<src:fragref linkend="src_inst_asm_sra"></src:fragref>
```

2.24. srli

2.24.1. Instruction definition

```
spec['useq']['inst']['srli'] = {
    'fullname' : 'srli',
    'Description' : 'Shift Right, Logical, using immediate value',
    'opcode1' : 0x8,
    'opcode3' : 0x6,
    'type' : 'Type_IV',
}
```

2.24.2. Instruction implementation

```
spec['useq']['inst']['srli']['impl'] = {
    'alu' : {
        'op' : 'srl',
        'sourcea' : 'rfa[rd]',
        'sourceb' : 'uk4', # R1 not used
    },
    'writeback' : {
        'source' : "alu",
        'dest' : "rfc[rd]",
    },
}
```

2.24.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.24.4. Specification list

```
<src:fragref linkend="src_inst_def_srli"></src:fragref>
<src:fragref linkend="src_inst_impl_srli"></src:fragref>
<src:fragref linkend="src_inst_asm_srli"></src:fragref>
```

2.25. srl

2.25.1. Instruction definition

```
spec['useq']['inst']['srl'] = {
    'fullname' : 'srl',
    'Description' : '16-bit Shift Right, Logical ',
    'opcode1' : 7,
    'opcode3' : 5,
    'type' : 'Type_III',
}
```

2.25.2. Instruction implementation

```
spec['useq']['inst']['srl']['impl'] = {
    'alu' : {
        'op' : 'srl',
        'sourcea' : 'rfa[rd]',
        'sourceb' : 'rbf[rs2]',
    },
    'flag' : {
        'carry_in' : 0,
        'carry' : 'keep',
    }
}
```

2.25.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.25.4. Specification list

```
<src:fragref linkend="src_inst_def_srl"></src:fragref>
<src:fragref linkend="src_inst_impl_srl"></src:fragref>
<src:fragref linkend="src_inst_asm_srl"></src:fragref>
```

2.26. sub2c

2.26.1. Instruction definition

```
spec['useq']['inst']['sub2c'] = {
    'fullname' : 'sub2c',
    'Description' : '16-bit subtraction with carry',
    'opcode1' : 7,
    'opcode3' : 9,
    'type' : 'Type_III',
}
```

2.26.2. Instruction implementation

```
spec['useq']['inst']['sub2c']['impl'] = {

    'alu' : {
        'op' : 'add',
        'sourcea' : 'rfa[rd]',
        'sourceb' : 'not_rfb[rs2]',
    },
    'flag' : {
        'carry_in' : 'not_carry',
        'carry' : 'update',
    }
}
```

2.26.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.26.4. Specification list

```
<src:fragref linkend="src_inst_def_sub2c"></src:fragref>
<src:fragref linkend="src_inst_impl_sub2c"></src:fragref>
<src:fragref linkend="src_inst_asm_sub2c"></src:fragref>
```

2.27. sub2

2.27.1. Instruction definition

```
spec['useq']['inst']['sub2'] = {
    'fullname' : 'sub2',
    'Description' : '16-bit signed subtraction',
    'opcode1' : 2,
    'type' : 'Type_I',
}
```

2.27.2. Instruction implementation

```
spec['useq']['inst']['sub2']['impl'] = {

    'alu' : {
        'op' : 'add',
        'sourcea' : 'rfa[rd]',
        'sourceb' : 'not_rfb[rs1]_or_uk4',
    },

    'flag' : {
        'carry_in' : 1,
        'carry' : 'update',
    }
}
```

2.27.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.27.4. Specification list

```
<src:fragref linkend="src_inst_def_sub2"></src:fragref>
<src:fragref linkend="src_inst_impl_sub2"></src:fragref>
<src:fragref linkend="src_inst_asm_sub2"></src:fragref>
```

2.28. sub3

2.28.1. Instruction definition

```
spec['useq']['inst']['sub3'] = {
    'fullname' : 'sub3',
    'Description' : '16-bit signed addition',
    'opcode1' : 0xD,
    'type' : 'Type_VII',
}
```

2.28.2. Instruction implementation

```
spec['useq']['inst']['sub3']['impl'] = {

    'alu' : {
        'op' : 'sub',
        'sourcea' : 'rfa[rs1]',
        'sourceb' : 'rbf[rs2]',
    },
    'flag' : { # some type_IV instructions will override that
        'carry_in' : 1,
        'carry' : 'update',
    },
}
```

2.28.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.28.4. Specification list

```
<src:fragref linkend="src_inst_def_sub3"></src:fragref>
<src:fragref linkend="src_inst_impl_sub3"></src:fragref>
<src:fragref linkend="src_inst_asm_sub3"></src:fragref>
```

2.29. sw

2.29.1. Instruction definition

```
spec['useq']['inst']['sw'] = {
    'fullname' : 'sw',
    'Description' : 'Store word',
    'opcode1' : 5,
    'type' : 'Type_II',
}
```

2.29.2. Instruction implementation

```
spec['useq']['inst']['sw']['impl'] = {

    'alu' : {
        'op' : 'add',
        'sourcea' : 'rfa[rs1]',
        'sourceb' : 'k4',
    },

    'writeback' : {
        'source' : "rfb[rd]",
        'dest' : "mem16",
    },
}
```

2.29.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.29.4. Specification list

```
<src:fragref linkend="src_inst_def_sw"></src:fragref>
<src:fragref linkend="src_inst_impl_sw"></src:fragref>
<src:fragref linkend="src_inst_asm_sw"></src:fragref>
```

2.30. xnor1

2.30.1. Instruction definition

```
spec['useq']['inst']['xnorr1'] = {
    'fullname' : 'xnorr1',
    'Description' : 'Bitwise xnor with r1 and immediate value',
    'opcode1' : 0x8,
    'opcode3' : 0x3,
    'type' : 'Type_IV',
}
```

2.30.2. Instruction implementation

```
spec['useq']['inst']['xnorr1']['impl'] = {
    'alu' : {
        'op' : 'xnor',
        'sourcea' : 'rfa[rd]',
        'sourceb' : 'rbf[r1]_or_uk4',
    },
}
```

2.30.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.30.4. Specification list

```
<src:fragref linkend="src_inst_def_xnorr1"></src:fragref>
<src:fragref linkend="src_inst_impl_xnorr1"></src:fragref>
<src:fragref linkend="src_inst_asm_xnorr1"></src:fragref>
```

2.31. xnor

2.31.1. Instruction definition

```
spec['useq']['inst']['xnor'] = {
```

```

    'fullname' : 'xnor',
    'Description' : '16-bit bitwise negated exclusive or',
    'opcode1' : 7,
    'opcode3' : 3,
    'type' : 'Type_III',
}

}

```

2.31.2. Instruction implementation

```

spec['useq']['inst']['xnor']['impl'] = {

    'alu' : {
        'op' : 'xnor',
        'sourcea' : 'rfa[rd]',
        'sourceb' : 'rbf[rs2]',
    },

    'flag' : {
        'carry_in' : 0,
        'carry' : 'keep',
    }
}

```

2.31.3. Assembler implementation

```

# ASM :
# No special implementation - following default for instruction type

```

2.31.4. Specification list

```

<src:fragref linkend="src_inst_def_xnor"></src:fragref>
<src:fragref linkend="src_inst_impl_xnor"></src:fragref>
<src:fragref linkend="src_inst_asm_xnor"></src:fragref>

```

2.32. xorrl1

2.32.1. Instruction definition

```

spec['useq']['inst']['xorrl1'] = {
    'fullname' : 'xorrl1',
    'Description' : 'Bitwise xor with r1 and immediate value',
    'opcode1' : 0x8,
    'opcode3' : 0x2,
    'type' : 'Type_IV',
}

```

```
}
```

2.32.2. Instruction implementation

```
spec['useq']['inst']['xorrl']['impl'] = {
    'alu' : {
        'op' : 'xor',
        'sourcea' : 'rfa[rd]',
        'sourceb' : 'rfb[r1]_or_uk4',
    },
}
```

2.32.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.32.4. Specification list

```
<src:fragref linkend="src_inst_def_xorrl"></src:fragref>
<src:fragref linkend="src_inst_impl_xorrl"></src:fragref>
<src:fragref linkend="src_inst_asm_xorrl"></src:fragref>
```

2.33. xor

2.33.1. Instruction definition

```
spec['useq']['inst']['xor'] = {
    'fullname' : 'xor',
    'Description' : '16-bit bitwise exclusive or',
    'opcode1' : 7,
    'opcode3' : 2,
    'type' : 'Type_III',
}
```

2.33.2. Instruction implementation

```
spec['useq']['inst']['xor']['impl'] = {
```

```
'alu'          : {
    'op'  : 'xor',
    'sourcea' : 'rfa[rd]',
    'sourceb' : 'rbf[rs2]',
},
'flag'        : {
    'carry_in' : 0,
    'carry'    : 'keep',
}
}
```

2.33.3. Assembler implementation

```
# ASM :
# No special implementation - following default for instruction type
```

2.33.4. Specification list

```
<src:fragref linkend="src_inst_def_xor"></src:fragref>
<src:fragref linkend="src_inst_impl_xor"></src:fragref>
<src:fragref linkend="src_inst_asm_xor"></src:fragref>
```


Internal GAS Pseudo-instructions

Pseudo-instructions (or synthetic instructions) are defined using native instructions. GAS can be configured through Archc to recognize those instructions directly and output corresponding native instructions. This simplifies assembly code writing and C compiler retargeting.



Important

The Archc code for pseudo-instructions recognized by GAS is generated automatically generated from the Python spec file. Don't edit Archc file directly !

3.1. zldi

3.1.1. Instruction definition

```
spec['useq']['pseudo_inst']['zldi'] = {
    'fullname' : 'zldi',
    'Description' : 'Load Immediate',
    'fields' : '%reg,%exp',
    'code' : """
        ldirl1 (%1>>4)      ;
        ori4   %0,r1,(%1 & 0x0F)  ;
    """
}
```

3.1.2. Specification list

```
<src:fragref linkend="src_inst_def_zldi"></src:fragref>
```

3.2. zjump

3.2.1. Instruction definition

```
spec['useq']['pseudo_inst']['zjump'] = {
    'fullname' : 'zjump',
    'Description' : 'Jump to an immediate address',
    'fields' : '%exp',
    'code' : """
        ldirl1 (%0>>4)      ;
        br    r1,(%0 & 0x0F)  ;
    """
}
```

3.2.2. Specification list

```
<src:fragref linkend="src_inst_def_zjump"></src:fragref>
```

Pseudo-instructions implemented as GAS macro

Some instructions can't be implemented directly in GAS using Archc. Therefore, they are implemented as GAS macros using the .macro .endm directives

4.1. 32-bit arithmetic instruction

4.1.1. zadd32 : 32-bit addition

Used to implement 32-bit addition for the C compiler

```
; fixme - no carry handling....  
.macro zadd32 src1,src2,dest  
    add3 \dest,\src1,\src2  
    add3 (\dest+1),(\src1+1),(\src2+1)  
.endm
```

```
<src:fragref linkend="src_inst_zadd32"></src:fragref>
```


Processing Element detailed instruction set



Note to the reader

The following sections contain description of all instructions used by the Processing Elements (PE). Behaviour of each instruction is described as a set of properties (expressed as a Python dictionary) that are used to generated Verilog code, Assembler and ArchC configuration code (for binutils tools like GAS...).

5.1. Instruction formats

5.1.1. Type I

5.1.1.1. Format definition

```

spec['pe']['inst_type']['Type_I']['format']= {
    'mem' : {'size' : 2,
              'offset' : 24,
            },
    'agen' : {'size' : 4,
              'offset' : 20,
            },
    'cond' : {'size' : 4,
              'offset' : 16,
            },
    'aluop' : {'size' : 4,
               'offset' : 12,
               'decode' : True, # Field is used for decoding
            },
    'rd' : {'size' : 4,
            'offset' : 8
          },
    'rsl' : {'size' : 4,
              'offset' : 4
            },
    'rs2' : {'size' : 4,
              'offset' : 0
            },
}
}

# default implementation
spec['pe']['inst_type']['Type_I']['impl']= {
    'rf' : {
}
}

```

```

'sela' : 'rs1',
'selb' : 'rs2',
'selc' : 'rd',
},
'writeback' : {
    'source' : "alu",
    'dest' : "rfc[rd]",
},
}

spec['useq'][['inst_type']['Type_I']['asm']] = '%reg, %reg, %exp';
spec['useq'][['inst_type']['Type_I']]['fields']= 'rd, rs1, uk4';
# just an helper for quick docbook generation - we could write some code to do it
automatically...
spec['useq'][['inst_type']['Type_I']]['docbook']= ('mem', 'agen', 'cond',
'aluop', 'rd', 'rs1', 'rs2');

```

5.1.1.2. Specification list

```
<src:fragref linkend="src_pe_inst_def_format_type_i"></src:fragref>
```

5.2. p_add

5.2.1. Instruction definition

```

spec['pe'][['inst']]['p_add'] = {
    'fullname' : 'p_add',
    'Description' : 'signed addition',
    'aluop' : 0x0,
    'type' : 'Type_I',
}

```

5.2.2. Instruction implementation

```

spec['pe'][['inst']]['p_add'][['impl']] = {

    'alu' : {
        'op' : 'add',
        'sourcea' : 'rfa[rs1]',
        'sourceb' : 'rbf[rs2]',
    },
    'flag' : {
        'carry_in' : 0,
        'carry' : 'update',
    },
}

```

5.2.3. Assembler implementation

```
# Special variant to support expression instead of "pure" register name
# - To be used in gas macro
spec['pe']['inst']['p_add']['asm'] = {
    'main'      : '\"p_add %reg,%reg,%reg\" + ',rd,rs1,rs2',
    'variant1'  : '\"p_add %exp,%exp,%exp\" + ',rd,rs1,rs2',
}
```

5.2.4. Specification list

```
<src:fragref linkend="src_pe_inst_def_p_add"></src:fragref>
<src:fragref linkend="src_pe_inst_impl_p_add"></src:fragref>
<src:fragref linkend="src_pe_inst_asm_p_add"></src:fragref>
```

5.3. p_or

5.3.1. Instruction definition

```
spec['pe']['inst']['p_or'] = {
    'fullname' : 'p_or',
    'Description' : 'Bitwise OR',
    'aluop'      : 0x1,
    'type'       : 'Type_I',
}
```

5.3.2. Instruction implementation

```
spec['pe']['inst']['p_or']['impl'] = {
    'alu'      : {
        'op' : 'or',
        'sourcea' : 'rfa[rs1]',
        'sourceb' : 'rbf[rs2]',
    },
    'flag'     : {
        'carry_in' : 0,
        'carry'    : 'keep',
    },
}
```

5.3.3. Assembler implementation

```
# Special variant to support expression instead of "pure" register name
# - To be used in gas macro
spec['pe'][['inst']['p_or']]['asm'] = {
    'main'      : '\\"p_or %reg,%reg,%reg\\' + ',rd,rs1,rs2',
    'variant1'  : '\\"p_or %exp,%exp,%exp\\' + ',rd,rs1,rs2',
}
```

5.3.4. Specification list

```
<src:fragref linkend="src_pe_inst_def_p_or"></src:fragref>
<src:fragref linkend="src_pe_inst_impl_p_or"></src:fragref>
<src:fragref linkend="src_pe_inst_asm_p_or"></src:fragref>
```

Appendix A. Revision History

Revision 0-0 Fri Sep 14 2012

Initial creation

Ronan Barzic ronan.barzic@atmel.com

Index

A

add2, 12
add2c, 11
add3, 13
andr1, 14

P

p_add, 50
p_or, 51

