

Transmitter Trb 8300 F/S & InPro® 8400/InPro® 8500 Sensor Series

Turbidity measurement system for low to medium concentrations

Technical Data



Trb 8300 F/S



InPro 8400



InPro 8500

Short description

The measuring system functions according to the principle of forward scattering of light, and consists of a transmitter Trb 8300 F/S and a sensor from the InPro 8400 family. The system is intended for inline detection of undissolved (suspended) substances in liquid media. Supplementary measurement of the scattered light at an angle of 90° using InPro 8500 sensors also provides information on a tendency basis about the possible size distribution of the particles responsible for the turbidity. The systems have been designed for measurement applications in industrial pipelines and provide important data for optimization, control and monitoring of production processes in the chemical, pharmaceutical, biotechnology and food & beverage industries.

Transmitter features

- Suitable for use in conjunction with the sensors InPro 8400 and InPro 8500
- Factory-defined, process and multipoint calibration routines
- Full text guided menu in three languages, including online help texts
- Three configurable and storable parameter sets with remote access
- Power requirement: 100...240 VAC or 24 VDC version
- RS232 interface for rapid programming with factory-defined sensor calibration data, as well as for updating of software
- Four galvanic isolated current outputs 0/4...20 mA according to NAMUR NE 43 Guideline
- Two programmable limit contacts, one alarm contact, wash contact and «HOLD» input

Sensor features


- Forward scattered light sensor with automatic color compensation (InPro 8400)
- Combined forward and 90° scattered light sensor with automatic color compensation (InPro 8500)
- Flow-through housing for installation in pipes DN25...DN100
- Rugged design in stainless steel
- Wide range of process adaptation methods
- Dirt-repellent sapphire window, suitable for CIP and SIP procedures
- Suited for installation in hazardous areas, Zones 1 and 2, Class 1, Div. 1 and 2 (certificate pending)
- Multipoint factory-defined calibration based on international turbidity standard using Formazin

Contents


Dimensional and installation drawings for transmitter Trb 8300 F/S	2
Technical specifications for transmitter Trb 8300 F/S	4
Ordering information for transmitter Trb 8300 F/S	6
Wiring diagram for transmitter Trb 8300 F/S	7
Dimensional and installation drawings for InPro 8400 / InPro 8500 sensors	10
Technical specifications for InPro 8400 / InPro 8500 sensors	13
Ordering information for InPro 8400 / InPro 8500 sensors	14

METTLER TOLEDO


Front




Side



Rear panel



Cutout for panel installation



Transmitter Trb 8300 F/S

Power requirement	100...240 V AC, max. 25 Watt, 47...63 Hz or 20...32 V DC, max. 25 Watt Data storage in non-battery supported EPROM in the event of power failure. Clock does not function without power supply.
Sensor connections	Input / output (approx. 5 V DC for sensor lamp) for optical sensors InPro 8400 or InPro 8500.
Measuring range	selectable: 0...400 FTU (Formazin Turbidity Units) 0...400 NTU (Nephelometric Turbidity Units) 0...100 EBC (Turbidity scale acc. to European Brewery Convention) 0...1000 ppm (Parts per millions solids content) 0...1.0 g/l (Solids content)
Measurement accuracy	≤ 1.0 %
Reproducibility of measured value	≤ 1.0 %
Resolution	0.01 FTU
Parameter sets	Three configurable parameter sets (A-C), storable and retrievable via software menu or by remote access via digital inputs.
Digital inputs	4 buffered digital inputs (0...5 V) – 1 digital input for «HOLD» function – 3 digital inputs for activating stored parameter sets A to C
System calibration (operational modes)	
Factory-defined calibration	Specific factory-set sensor data can be imported via RS232 interface or manually via keypad.
Process calibration	Single-point calibration simultaneously with sampling (adjustment of offset or slope, user-defined).
Multipoint calibration	Automatic 2, 3, 4 or 5 point calibration using calibration solutions of defined concentration in order to linearize the measurement curve.
Preset calibration parameter	Software reset restores calibration data to factory-set sensor data.
Password protection	Password-protected menu access for different operator levels (Master, User 1 and 2), able to be activated.
Sensor diagnostics	Lamp: indication on display of length of time switched on Sensor: indication on display of the photoelectric currents for transmitted light. 12° forwards scattered light and 90° scattered light (InPro 8500 only)
Current outputs	Four analog outputs 0/4...20 mA. Burden max. 500 Ω, galvanic isolated. Accuracy ± 0.05 mA. The outputs can be freely assigned to individual parameter sets, with choice of scaling in linear, bi-linear, logarithmic or dual-range format.

Transmitter Trb 8300 F/S

Alarm contact	Relay contact, SPDT, floating
Contact capacity	AC< 250 V/< 5 A DC< 30 V/< 5 A
Contact function	N/C (fail-safe type)
Alarm delay	000...600 s
Wash contact	Relay contact, SPDT, floating
	AC< 250 V/< 5 A DC< 30 V/< 5 A
Contact function	N/O or N/C
Cleaning interval	0.0...999.9 h (0.0 h = cleaning function switched off)
Duration of cleaning	000...600 s
Limit values (2)	2 relay contacts, SPDT, floating
Contact capacity	AC< 250 V/< 5 A DC< 30 V/< 5 A
Contact function	N/O or N/C
Delay	000...600 s
Switching point	hi-hi / hi-lo / lo-lo
Hysteresis	0.0...50.0%
Digital interface	For programming with factory-defined sensor calibration coefficients, updating of main program software and for printing of instrument configuration.
RS232 standard	max. cable length 15 m
Baud Rate	1200, 2400, 4800, 9600, 19.2k and 38.4k
Parity	odd, even or none
Display	Liquid cristal display (LCD), 20 alphanumerical characters x 4 lines, backlit
Keypad	20 keys, membrane-type keypad
Languages	Selectable via software: German, English or French for menu and Help texts
Diagnostic functions	Sensor Lamp mA outputs Display Keypad Instrument Serial interface Contacts Self-test

Transmitter Trb 8300 F/S


Data retention	Configuration and calibration data in non-battery supported, non-volatile storage.
CE	
Emission:	EN 55011 Group I, Class A ISM emissions.
Immunity:	EN 50082-2 EMC heavy industrial generic immunity standard.
Safety:	IEC 61010-1 Safety requirements for electrical equipment for measurement, control and laboratory use
US UL	3111-1 Electrical Measuring and test Equipment
CAN / CSA	C22.2, No. 1010.1
Nominal operating conditions	
Ambient temperature	-10...+55 °C (14...131 °F)
Transport and storage temperature	-20...+80 °C (-4...176 °F)
Relative humidity	0...80 % at 31 °C (88 °F), linear decline to 50 % at 40 °C (122 °F)
Enclosure	
Composite:	ABS-PC, resistant to UV and chemicals
Cutout:	for panel installation: 96 x 96 mm (3.78" x 3.78") 1/4 DIN
Dimensions:	H: 125 mm x W: 114 mm x L: 162 mm (H: 4.92" x W: 4.50" x L: 6.39")
Protection:	sealed face, IP 65
Weight:	0.9 kg (2 lbs.)

Ordering information

Designation	Order no.
Transmitter	
Transmitter Trb 8300 F/S, 100...240 V AC version	52 800 865
Transmitter Trb 8300 F/S, 20...32 V DC version	52 800 866
Accessory	
IP 66 field-type enclosure for wall mounting, incl. 5 pcs. PG11 cable gland (H = 200, W = 250, L = 230 mm / H = 7.87", W = 9.84", L = 9.10")	52 800 867
Spare parts	
10-terminal plug-in connector (TB2 and TB3)	52 800 251
6-terminal plug-in connector (TB5 and TB6)	52 800 252
Fuse, 0.5 A slow-blow, 5 x 20 mm (Littlefuse 215.500 or equivalent)	52 800 253
Screw for panel mounting (6...32 x 7/16", total 4 pcs. necessary)	52 800 254
Screw for front panel (total 2 pcs. necessary)	52 800 255
Lock washer for front panel (2 pcs.)	52 800 256
Liquid crystal display module (spacer(s) to be ordered separately)	52 800 257
Display standoffs (4 pcs.)	52 800 258


Terminal assignment

Strip	Terminal	Connection
TB1	⊕	Ground
	N	Neutral
	L	Phase



Terminal assignment Trb 8300 F/S 20...32 V DC

Strip	Terminal	Connection
TB1		Ground
	PS-	DC minus
	PS+	DC plus



Sensor connections


Strip	Terminal	Connection
TB7	12	Lamp voltage plus (grey/rose)
	13	Lamp voltage minus (blue/red)
	14	Shielding
TB9	1	Photoelectric current transmitted light (brown)
	2	Photoelectric current transmitted light (white)
	3	Shielding (black)
	4	Photoelectric current forward scattered light (yellow)
	5	Photoelectric current forward scattered light (green)
	6	Shielding (black)
	InPro 8500 only	
	7	Photoelectric current 90° scattered light (yellow)
	InPro 8500 only	
	8	Photoelectric current 90° scattered light (green)
	InPro 8500 only	

Other


Strip	Terminal	Connection
TB2	1	Not to be used!
	2	Parameter sets A, B and «HOLD» (Digital 2)
	3	Not to be used!
	4	Parameter set B (Digital 1)
	5	Not to be used!
	6	«HOLD» (Digital 1)
	7	Parameter set A (Digital 1)
	8	RS 232 ground
	9	RS 232, receive
	10	RS 232, transmit
TB3	11	Not to be used!
	12	Parameter set C (Digital 2)
	13	Parameter set C (Digital 1)
	14	Not to be used!
	15	Current output 4+
	16	Current output 3+
	17	Current output –
	18	Current output –
	19	Current output 2+
	20	Current output 1+
TB5	1	Alarm, normally closed
	2	Alarm «Common»
	3	Alarm, normally open
	4	Wash, normally closed
	5	Wash, «Common»
	6	Wash, normally open
TB6	7	Limit value 1, normally closed
	8	Limit value 1, «Common»
	9	Limit value 1, normally open
	10	Limit value 2, normally closed
	11	Limit value 2, «Common»
	12	Limit value 2, normally open

Sensor drawings

InPro 8400 MT



InPro 8500 MT



All dimensions in mm, subject to changes!

Dimensions InPro 8400/InPro 8500 MT and process pressures

InPro 8400/InPro 8500 MT flange

DIN 2633/PN 16, DN25...DN50 = 16 bar, > DN50 = 10 bar

± 1 mm	Z	Y	X	D	G	W
DN25	184	184	184	169	34.5	800
DN40				177	38.5	
DN50				183	39.5	
DN65	193	193	193	180	42.0	
DN80	199	199	199	190	45.0	
DN100	212	212	212	194	47.0	900

InPro 8400/InPro 8500 MT – milk fitting

DIN 11851, 10 bar

± 1 mm	Z	Y	X	D	W
DN25	184	184	184	151	800
DN40				159	
DN50				163	
DN65	193	193	193	170	
DN80	199	199	199	180	
DN100	212	212	212	198	900

InPro 8400/InPro 8500 MT flange

ANSI B 16.5 / 150 lb in², 1"…2" = 16 bar, > 2" = 10 bar

± 1 mm	Z	Y	X	D	G	W
1"	184	184	184	204.2	53.9	800
1 1/2"				217.0	57.0	
2"				220.0	56.9	
3"	199	199	199	229.8	61.0	
4"	212	212	212	242.4	67.3	900

InPro 8400/InPro 8500 MT APV flange

10 bar

± 1 mm	Z	Y	X	D	G	W
DN25	184	184	184	141	26.5	800
DN40	184	184	184	141	26.5	800
DN50				141	26.5	
DN65	193	193	193	138	29.0	
DN80	199	199	199	138	29.0	
DN100	212	212	212	138	29.0	900



InPro 8400/InPro 8500 MT NPT thread

150 lb in²



± 1 mm	Z	Y	X	H	W
1/2"	184	184	184	110.7	800
1"	184	184	184	124.7	800

Sensor drawings

InPro 8400 MT (Ex version)



InPro 8500 MT (Ex version)



All dimensions in mm, subject to changes!

Dimensions InPro 8400/8500 MT (Ex version) and process pressures

InPro 8400/InPro 8500 MT flange

DIN 2633/PN 16, DN25...DN50 = 10 bar, > DN50 = 10 bar

± 1 mm	V	U	T	D	G	W
DN25	226	226	226	169	34.5	800
DN40				177	38.5	
DN50				183	39.5	
DN65	235	235	235	180	42.0	
DN80	241	241	241	190	45.0	
DN100	254	254	254	194	47.0	900

InPro 8400/InPro 8500 MT – milk fitting

DIN 11851, 10 bar

± 1 mm	V	U	T	D	W
DN25	226	226	226	151	800
DN40				159	
DN50				163	
DN65	235	235	235	170	
DN80	241	241	241	180	
DN100	254	254	254	198	900

InPro 8400/InPro 8500 MT flange

ANSI B 16.5 / 150 lb in², 1"...2" = 10 bar, > 2" = 10 bar

± 1 mm	V	U	T	D	G	W
1"	226	226	226	204.2	53.9	800
1 1/2"				217.0	57.0	
2"				220.0	56.9	
3"	241	241	241	229.8	61.0	
4"	254	254	254	242.4	67.3	900

InPro 8400/InPro 8500 MT APV flange

10 bar

± 1 mm	V	U	T	D	G	W
DN25	226	226	226	141	26.5	800
DN40				141	26.5	
DN50				141	26.5	
DN65	235	235	235	138	29.0	
DN80	241	241	241	138	29.0	
DN100	254	254	254	138	29.0	900


InPro 8400/InPro 8500 MT NPT thread

150 lb in²

± 1 mm	Z	Y	X	H	W
1/2"	226	226	226	110.7	800
1"	226	226	226	124.7	800

Dimensions InPro 8400 T, N, TC and process pressures

InPro 8400 T (Tuchenhagen Varivent®-inline)




DN40...DN50 = 25 bar, DN65...DN80 = 16 bar, DN100 = 10 bar

± 3 mm	Z	Y	D	W
DN 40/1.5" OD	190	190	180	800
DN50/2" OD	197	197		
DN65	205	205	250	
DN80/3" OD	213	213		
DN100/4" OD	222	222		

Attention: Dimensions do not include adaptations

InPro 8400 N (Neumo BioControl®)




16 bar

± 1 mm	Z	Y	D	W
DN 40	202	202	180	800
DN50	208	208	200	
DN65	216	216		
DN80	222	222		
DN100	235	235		

Attention: Dimensions do not include adaptations

InPro 8400 TC (Tri-Clover Tri-Clamp)



3/4" ... 3" = 16 bar, 4" = 13 bar

± 1 mm	Z	Y	D	W
3/4"	185	185	152.4	800
1"	191	191		
1 1/2"	194	194	165.1	
2"	200	200		
3"	213	213	228.6	900
4"	216	216		

All dimensions in mm, subject to changes!

Sensor

	InPro® 8400	InPro® 8500
Measuring principle	Forward light scattering (12°)/ transmitted light (Ratio measurement to compensate for color influences)	Forward light scattering (12°)/ transmitted light and 90° scattered light/ (Ratio measurement to compensate for color influences)
Measuring range	0...400 FTU 0...100 EBC 0...1000 ppm or 0...1.0 g/l solid matter, diatomaceous earth as reference	0...400 FTU 0...400 NTU 0...100 EBC 0...1000 ppm or 0...1.0 g/l, solid matter, diatomaceous earth as reference
Process adaptation, alternatives:	InPro 8400 MT: Flange DIN 2633 Flange ANSI B 16.5 Flange APV Milk fitting DIN 11851 or NPT thread InPro 8400 T: Tuchenhagen Varivent inline housing with welding ends InPro 8400 N: Neumo BioControl Flow-through housing with welding ends InPro 8400 TC: Tri-Clover housing with Tri-Clamp connections	InPro 8500 MT: Flange DIN 2633 Flange ANSI B 16.5 Flange APV Milk fitting DIN 11851 or NPT thread
Nominal diameters	see tables on pages 10 to 12	see tables on pages 10 to 12
Wetted parts	InPro 8400 MT/InPro 8400 T/ InPro 8400 N: Sensor housing: 1.4404 Meas. window: Sapphire Seals: Viton®-FDA, Kalrez®-FDA or EPDM-FDA InPro 8400 TC: Sensor housing: 316 SS Meas. window: Sapphire Seals: Viton®-FDA, Kalrez®-FDA or EPDM-FDA	InPro 8500 MT: Sensor housing: 1.4404 Meas. window: Sapphire Seals: Viton®-FDA, Kalrez®-FDA or EPDM-FDA
Surface roughness wetted parts made of stainless steel	InPro 8400 MT: ≤ 3.2 µm InPro 8400 T: ≤ 0.8 µm InPro 8400 N: ≤ 0.8 µm InPro 8400 TC: ≤ 32 Ra (≤ 0.8 µm)	InPro 8500 MT: ≤ 3.2 µm

Sensor

	InPro® 8400	InPro® 8500
Operating conditions		
Pressure range	depending upon process adaptation, see tables on pages 10 to 12	depending upon process adaptation, see tables on pages 10 to 12
Temperature range	0...140 °C (284 °F)	0...140 °C (284 °F)
Steam-sterilizable	yes (140 °C [284 °F]/ 15 min. / day)	yes (140 °C [284 °F]/ 15 Min. / day)
Suited for CIP	yes	yes
Protection rating	IP 65	IP 65
Cable lengths	5...100 m in 5 m intervals	5...100 m in 5 m intervals
Options		
Ex-classified	according to ATEX or FM (pending)	according to ATEX or FM (pending)

Ordering information

For the configuration of a sensor with exact specifications such as relative to process adaption, pipe line size, seal materials and other options, please use the following configuration data sheets:

Configuration data sheet

InPro 8400 MT: METTLER TOLEDO flow-through housing

Field	Code	Specification
Line size of sensor with metric connections		
C	0	DN25
C	2	DN40
C	3	DN50
C	4	DN65
C	5	DN80
C	6	DN100
or line size diameter of sensor housing with inch-system connections		
C	8	1/2"
C	B	1"
C	C	1 1/2"
C	D	2"
C	E	3"
C	F	4"
D	0	Not applicable
Metric process connection		
E	0	Flange DIN 2633
E	1	Milk fitting DIN11851
E	2	APV flange (flat)
or inch-system process connection		
E	4	ASA- (ANSI) flange
E	5	NPT thread (only available in 1/2" or 1" version)
Optical windows		
F	0	Standard, sapphire window
Seals for windows / FDA-compliant		
G	0	Viton®
G	2	EPDM
G	3	Kalrez®
Electrical specification		
H	0	Non-(Ex)-proof
H	2	Hazardous areas, Zone 1 and 2 (ATEX certification)
H	3	Hazardous areas, Class 1, Div. 1 and 2 (FM certification, pending)
I	0	Not applicable
Cable (max.100 m in 5 m intervals, cable sets for lamps and detector)		
J	0	5 m (16.4 ft) , standard
J	9	For cable sets longer than 5 m, total length: ... m
Standard specification		
K	2	Air-purge connection for optical system (for process temperatures T < 15 ° C [59 ° F] or > 100 ° C [212 ° F])
K	3	Product certificates (calibration, CE, Ex-classified documentation, ...)

Ordering code

InPro 8400 MT –		0		0			0		2-3
Field	C	D	E	F	G	H	I	J	K

Configuration data sheet

InPro 8400 T: Tuchenhausen inline Varivent housing

Field	Code	Specification
Line size of sensor housing according to DIN11850		
C	2	DN40
C	3	DN50
C	4	DN65
C	5	DN80
C	6	DN100
or line size of sensor housing according to OD		
C	C	1 1/2"
C	D	2"
C	E	3"
C	F	4"
Surface finish of wetted parts made of stainless steel		
D	1	Standard, ≤ 0.8 µm
Process connection		
E	B	Standard, welding ends
Optical window		
F	0	Standard, sapphire window
Seals for windows / FDA-compliant		
G	0	Viton®
G	2	EPDM
G	3	Kalrez®
Electrical specifications		
H	0	Non-(Ex)-proof
H	2	Hazardous areas, Zone 1 and 2 (ATEX certification)
H	3	Hazardous areas, Class 1, Div. 1 and 2 (FM certification, pending)
Material of seals of Varivent connection plates, FDA-compliant		
I	0	EPDM
I	1	FPM (Viton®)
Cable (max.100 m in 5 m intervals, cable sets for lamps and detector)		
J	0	5 m (16.4 ft), standard
J	9	For cable sets longer than 5 m, total length: ... m
Standard specifications		
K	2	Air-purge connection for optical system (for process temperatures T < 15 °C [59 °F] or > 100 °C [212 °F])
K	3	Product certificates (calibration, CE, 3.1B material certificate,...)

Ordering code

InPro 8400 T –		1	B	0					2-3
Field	C	D	E	F	G	H	I	J	K

Configuration data sheet

InPro 8400 N: Neumo BioControl housing

Field	Code	Specification
Line size of sensor housing according to DIN11866 line A, DIN11850		
C	2	DN40
C	3	DN50
C	4	DN65
C	5	DN80
C	6	DN100
Surface finish of wetted parts made of stainless steel		
D	0	Standard, $\leq 0.8 \mu\text{m}$
Process connections		
E	B	Standard, welding ends
Optical windows		
F	0	Standard, sapphire window
Seals for windows / FDA-compliant		
G	0	Viton®
G	2	EPDM
G	3	Kalrez®
Electrical specifications		
H	0	Non-(Ex)-proof
H	2	Hazardous areas, Zone 1 and 2 (ATEX certification)
H	3	Hazardous areas, Class 1, Div. 1 and 2 (FM certification, pending)
Material of seals of BioControl connection plates, FDA-compliant		
I	0	EPDM
I	1	FPM (Viton®)
Cable (max. 100 m in 5 m intervals, cable sets for lamps and detector)		
J	0	5 m (16.4 ft.), standard
J	9	For cable sets longer than 5 m, total length: ... m
Standard specifications		
K	2	Air-purge for optical system (for process temperatures $T < 15^\circ\text{C}$ [59°F] or $> 100^\circ\text{C}$ [212°F])
K	3	Product certificates (calibration, CE, 3.1B material certificate,...)

Ordering code

InPro 8400 N –		0	B	0					2-3
Field	C	D	E	F	G	H	I	J	K

Configuration data sheet

InPro 8400 TC: Tri-Clover sight-glass housing

Field	Code	Specification							
Line size of sensor housing									
C	A	3/4"							
C	B	1"							
C	C	1 1/2"							
C	D	2"							
C	E	3"							
C	F	4"							
Surface finish of wetted parts made of stainless steel									
D	0	Standard, ≤ 32 Ra (≤ 0.8 µm)							
D	1	Special, ≤ 15 Ra (≤ 0.4 µm)							
Process connections									
E	A	Standard, Tri-Clamp connection L 14 AM 7							
Optical windows									
F	0	Standard, sapphire window							
Seals for windows / FDA-compliant									
G	0	Viton®							
G	2	EPDM							
G	3	Kalrez®							
Electrical specifications									
H	0	Non-(Ex)-proof							
H	2	Hazardous areas, Zone 1 and 2 (ATEX certification)							
H	3	Hazardous areas, Class 1, Div. 1 and 2 (FM certification, pending)							
Material of seals of Tri-Clamp connection plates, FDA-compliant									
I	0	EPDM							
I	2	PTFE							
Cable (max. 100 m in 5 m intervals, cable sets for lamps and detector)									
J	0	5 m (16.4 ft.), standard							
J	9	For cable sets longer than 5 m, total length: ... m							
Standard specifications									
K	2	Air-purge connection for optical system (for process temperatures T < 15 °C [59 °F] or > 100 °C [212 °F])							
K	3	Product certificates (calibration, CE, Ex-classified documentation,...)							
Ordering code									
InPro 8400 TC –									
Field	C	D	E	F	G	H	I	J	2-3 K

Configuration data sheet

InPro 8500 MT: METTLER TOLEDO flow-through housing

Field	Code	Specification
Line size of sensor housing with metric connections		
C	0	DN25
C	2	DN40
C	3	DN50
C	4	DN65
C	5	DN80
C	6	DN100
or line size of sensor housings with inch-system connections		
C	8	1/2"
C	B	1"
C	C	1 1/2"
C	D	2"
C	E	3"
C	F	4"
D	0	Not applicable!
Metric connections		
E	0	Flange DIN 2633
E	1	Milk fitting DIN11851
E	2	APV flange (flat)
or inch-system connections		
E	4	ASA- (ANSI) flange
E	5	NPT thread (only available in 1/2" or 1" versions!)
Optical window		
F	0	Standard, sapphire window
Seals for windows / FDA-compliant		
G	0	Viton®
G	2	EPDM
G	3	Kalrez®
Electrical specifications		
H	0	Non(Ex)-proof
H	2	Hazardous areas, Zone 1 and 2 (ATEX certification)
H	3	Hazardous areas, Class 1, Div. 1 and 2 (FM certification, pending)
I	0	Not applicable
Cable (max. 100 m in 5 m intervals, cable sets for lamps and detector)		
J	0	5 m (16.4 ft.), standard
J	9	For cable sets longer than 5 m, total length: ... m
Standard specifications		
K	2	Air-purge connection for optical system (for process temperatures T < 15 °C [59 °F] or > 100 °C [212 °F])
K	3	Product certificates (calibration, CE, 3.1B material certificate, Ex-classified documentations,...)

Ordering code

InPro 8500 MT –		0		0			0		2 - 3
Field	C	D	E	F	G	H	I	J	K

Sensor spare parts

Designation	Bestell-Nr.
InPro8400/InPro8500 measuring lamp	52 800 889
InPro8400/InPro8500 sapphire window	52 800 890
Window sealing, O-ring, Viton®	52 750 136
Window sealing, O-ring, EPDM	52 750 137
Window sealing, O-ring, Kalrez®	52 750 138
InPro8400/InPro8500 lamp kit	52 800 886
InPro8400/InPro8500 detector kit FW (12°)	52 800 887
InPro8500 detector kit SW (90°)	52 800 888

[illegible]

[illegible]

[illegible]

METTLER TOLEDO Market Organizations

Sales and Service:

Australia

Mettler-Toledo Ltd.
220 Turner Street
Port Melbourne
AUS - 3207 Victoria
Phone +61 39 644 57 00
Fax +61 39 645 39 35
e-mail mtausprocess@mt.com

Austria

Mettler-Toledo GmbH
Favoritner Gewerberger 17
A - 1100 Wien
Phone +43 1 604 19 80
Fax +43 1 604 28 80
e-mail infoprocess.mtat@mt.com

Brazil

Mettler-Toledo Ind. e Com. Ltda.
Alameda Araguaia
451 - Alphaville
BR - 06455-000 Barueri / SP
Phone +55 11 4166 74 00
Fax +55 11 4166 74 01
e-mail sales@mettler.com.br
service@mettler.com.br

China

Mettler-Toledo Instruments
(Shanghai) Co. Ltd.
589 Gui Ping Road
Cao He Jing
CN - 200233 Shanghai
Phone +86 21 64 85 04 35
Fax +86 21 64 85 33 51

Croatia

Mettler-Toledo d.o.o.
Mandlova 3
HR - 10000 Zagreb
Phone +385 1 292 06 33
Fax +385 1 295 81 40
e-mail mt-zag@zg.tel.hr

Czech Republic

Mettler-Toledo spol s.r.o.
Trebohosticka 2283 / 2
CZ - 100 00 Praha 10
Phone +420 2 72 123 151
Fax +420 2 72 123 170
e-mail sales.mtcz@mt.com

Denmark

Mettler-Toledo A/S
Naverland 8
DK - 2600 Glostrup
Phone +45 43 27 08 00
Fax +45 43 27 08 28
e-mail mtdk@post10.tele.dk
lsl@mts.mt.com

France

Mettler-Toledo
Analyse Industrielle Sarl
30, Boulevard Douaumont
BP 949
F - 75017 Paris Cedex 17
Phone +33 1 47 37 06 00
Fax +33 1 47 37 46 26
e-mail mtpro-f@mt.com
mtai@mtprof-mt.com

Germany

Mettler-Toledo GmbH
Prozeßanalytik
Ockerweg 3
D - 35396 Gießen
Phone +49 641 507 333
Fax +49 641 507 397
e-mail prozess@mt.com

Great Britain

Mettler-Toledo LTD
64 Boston Road, Beaumont Leys
GB - LE4 1AW Leicester
Phone +44 116 235 7070
Fax +44 116 236 5500
e-mail enquire.mtuk@mt.com

Hungary

Mettler-Toledo Kereskedelmi KFT
Teve u. 41
HU - 1139 Budapest
Phone +36 1 288 40 40
Fax +36 1 288 40 50

Italy

Mettler-Toledo S.p.A.
Via Vialba 42
I - 20026 Novate Milanese
Phone +39 02 333 321
Fax +39 02 356 2973
e-mail mettler.toledo@interbusiness.it

Japan

Mettler-Toledo K.K.
Process Division
5F Tokyo Ryutsu Center, Annex B
6-1-1 Heiwajima, Ohta-ku
JP - 143-0006 Tokyo
Phone +81 3 5762 07 06
Fax +81 3 5762 09 71
e-mail yasuo.watanabe@mt.com

Mexico

Mettler-Toledo S.A. de C.V.
Pino No. 350, Col. Sta.
MA. Insurgentes, Col Atlampa
MX - 06450 México D.F.
Phone +52 5 541 33 00
Fax +52 5 541 04 02
e-mail mario.roca@mt.com

Poland

Mettler-Toledo (Poland) Sp.z.o.o.
ul. Iwonicka 39
PL - 02-924 Warszawa
Phone +48 22 651 92 32
Fax +48 22 651 71 72
e-mail polska@mt.com

Russia

Mettler-Toledo ZAO
Sretenskij Bulvar 6/1
Office 6
RU - 101000 Moscow
Phone +7 095 921 92 11
Fax +7 095 921 63 53
+7 095 921 78 68
e-mail inforus@mt.com

Singapore

Mettler-Toledo (S) Pte. Ltd.
Block 28
Ayer Rajah Crescent # 05-01
SG - 139959 Singapore
Phone +65 6890 00 11
Fax +65 6890 00 12
+65 6890 00 13
e-mail ashley.kong@mt.com

Slovakia

Mettler-Toledo s.r.o.
Bulharska 61
SK - 82104 Bratislava
Phone +421 743 42 74 96
Fax +421 743 33 71 90
e-mail predaj@mt.com

Slovenia

Mettler-Toledo d.o.o.
IOC Trzin, Peske 12
SI - 1236 Trzin
Phone +386 61 162 18 01
Fax +386 61 162 17 89
e-mail cipot@mtslo.mt.com
racman@mettler-toledo.si

Sweden

Mettler-Toledo AB
Virkesvägen 10
Box 92161
SE - 12008 Stockholm
Phone +46 8 702 50 00
Fax +46 8 642 45 62
e-mail sales.mts@mt.com

Switzerland

Mettler-Toledo (Schweiz) AG
Im Langacher
Postfach
CH - 8606 Greifensee
Phone +41 1 944 45 45
Fax +41 1 944 45 10
e-mail info.ch@mt.com
info.ola.ch@mt.com

Thailand

Mettler-Toledo Thailand
1. Floor, 272 Block A3
Raintree Office Garden
Rama 9 Rd. Kuay Kwang
TH - 10310 Bangkok
Phone +66 2 723 03 00
Fax +66 2 719 64 79
e-mail mettler@samart.co.th

USA / Canada

Mettler-Toledo Ingold, Inc.
36 Middlesex Turnpike
Bedford, MA 01730, USA
Phone +1 781 301 8800
Toll free +1 800 352 8763
Fax +1 781 271 0681
e-mail mtprou@mt.com



Management System
certified according to
ISO 9001 / ISO 14001

Subject to technical changes.
© Mettler-Toledo GmbH, Process Analytics
09 / 03 - Printed in Switzerland. 52 800 877

Mettler-Toledo GmbH, Process Analytics
Industrie Nord, CH - 8902 Urdorf
Tel. + 41 1 736 22 11, Fax +41 1 736 26 36

www.mtpro.com