


## We've Taken Performance to A New Peak.

INTRODUCING THE NEW 4500B PEAK POWER ANALYZER

triggering -8.4" TFT color LCD display -100 ps timebase resolution -Automatic peak-to-peak, delay-by-time and delay



# BOON

A WIRELESS TELECOM

T&amp;MW NEWS PRODUCTS COMPANIES WEB

SEARCH

[Home](#) | [Archives](#) | [Blogs](#) | [Advertising](#) | [Editorial Calendar](#) | [About Us](#) | [E-mail Us](#) | [Subscriptions](#) | T&MW C

Subscribe  
FOR FREE

Print and Digital  
Editions

Click here for a chance  
to win a 20GB Apple  
iPod from T&MW


[Free print subscription](#)


### MORE ARTICLES

[UL sets up Singapore office](#)

06/05/2006, Test & Measurement World

[Azimuth provides platform for 802.11n functional testing](#)

06/01/2006, Test & Measurement World

[ADS and Genesys RF tools get design links](#)

05/30/2006, Test & Measurement World

[Network Processing Forum to merge with Optical Internetworking Forum](#)

05/06/2006, Test & Measurement World

## Wi-Fi metrics

*The IEEE 802.11T Task Group is pursuing standardization of wireless test methods and metrics.*

Fanny Mlinarsky, Azimuth Systems, Acton, MA -- *Test & Measurement World*, 10/1/2004

The IEEE 802.11 Wireless Local Area Network (WLAN) technology, commonly known as Wi-Fi, has been steadily gaining popularity, keeping users on the go productively connected at airports, in hotels, and even in front of living-room TV sets. Most of us who have experienced the freedom and flexibility of wireless connectivity have no wish to return to tethered networking.

So far, wireless networking has been largely confined to the airport, hotel, coffee-shop, and small-office home-office (SOHO) markets, where performance is less important than cost. The new target for the wireless industry is the lucrative enterprise market, but those of us who yearn for 802.11 to take hold in the enterprise have to wait until the technology proves itself sufficiently robust and ready to carry demanding mission-critical applications. In enterprises, network performance impacts productivity, and IT executives won't make the decision to deploy 802.11 lightly.

Formal, standardized test procedures could help convince IT skeptics that 802.11 equipment can deliver the throughput, client capacity, security, and fault tolerance that corporate environments require. Recognizing that the definition of test methods and metrics is a timely and important undertaking, the IEEE 802 committee in July formed the IEEE 802.11T Task Group, which is charged with developing a test-specification document titled, "Recommended Practice for the Evaluation of 802.11 Wireless Performance."

Proper testing in accordance with this document will provide end users with an objective means of evaluating functionality and performance of 802.11 products, and it will help guide the Wi-Fi industry toward making 802.11 products faster, stronger, and more resilient to adverse network conditions—in short, ready to face the challenges and demands of the enterprise.

T&amp;M

An:  
A2:  
A2:  
at /  
hav  
unc  
phy  
anc  
cor

eCards

TestLit Review

**SUBSCRIPTIONS**

Subscription Info

Subscribe to Newsletters

**REGISTRATION**

Register

**REED ELECTRONICS GROUP WEBSITES**

ECN

EDN

Electronic Business

Electronic News

In-Stat

Semiconductor International

Reed Electronics Group

**REED BUSINESS INFORMATION WEBSITES**

Control Engineering

Design News

Industrial Distribution

Kellysearch

Logistics Management

Manufacturing.net

Modern Materials Handling

Purchasing

Purchasing Data

Supply Chain Mgmt Review

**The challenges of wireless test**

Originally touted as "wireless Ethernet," IEEE 802.11 (Ref. 1) evolved to be more elaborate than its IEEE 802.3 wireline counterpart. The inherent mobility and erratic transmission environment of Wi-Fi require new media access control (MAC) layer protocols that do not exist in the wired world. These protocols have added significantly to the number of test metrics that are needed to qualify a product's performance and behavior. A rough count shows that wireless-LAN metrics outnumber traditional Ethernet metrics 5 to 1.




Figure 1. Three measurements performed an open air (top) give diverging results, while the same measurements performed in a controlled and shielded RF environment (bottom) give identical results. A controlled RF environment can save time and facilitate results correlation among different test labs.

According to Paul Nikolich, chair of the IEEE 802 committee, "A test specification is particularly important for 802.11 given the complexity of the protocol and the challenges of wireless test. Standard test-methodology guidelines can help the end-user community evaluate product specifications and performance."

The testing of 802.11 devices and systems for performance and stability is a challenge for the industry. The 802.11 protocol's complexity brings with it a corresponding test complexity that is further compounded by the prevalence of RF interference and the inherent mobility of the wireless devices.

RF interference makes it difficult to obtain repeatable results that can be correlated among multiple laboratories. Interference, originating from sources including phones, microwave ovens, and adjacent wireless networks, can force the devices to retransmit or to continuously vary the data rate, thereby producing random results. **Figure 1** provides examples of throughput measurements on data forwarded by an 802.11 access point (AP) onto the Ethernet interface.

You could combat interference by performing measurements in walk-in shielded EMI chambers, but such chambers are impractical for 802.11 roaming tests. Tests of mobility-related protocols, such as roaming and rate adaptation, must be performed while the device is in motion, often rolling on a cart in uncontrolled, interference-prone settings.

So how do you deal with mobility and interference when testing wireless systems? The 802.11T committee is considering several solutions. One is based on a cabled environment that uses programmable RF attenuators to

ma

A2  
Em  
Se  
A2  
is a  
Se  
pro  
des  
dev  
Wit

Fro  
Pro  
Key  
Cor  
ava  
res  
dist  
line  
32C  
ma  
95.

Wh  
CP  
Dis  
ber  
suc  
Sor  
per  
arc  
set

VG  
AS  
Wh  
all  
mo  
sili  
syn  
opt  
cor

emulate variable distances between devices.

In such an environment, each device in a test setup is placed in a shielded chamber for isolation. RF cables connect the antenna ports of each device under test to other devices through programmable attenuators (**Figure 2**) that emulate distance by controlling the signal levels at the antenna ports.

Shielding and filtering protect the test setup from outside interference and achieve device-to-device isolation. Devices can connect through a network of attenuators and combiners to emulate complicated multi-BSS topologies. (A BSS, or Basic Service Set, is a network of one access point and the stations associated with it.)



### IEEE 802.11T's mission

The goal of the 802.11T project is to provide a set of performance metrics, measurement methodologies, and test conditions to enable manufacturers, test labs, service providers, and users to measure the performance of 802.11 WLAN

devices and networks at the component and application level. The document developed by this group will supply IT managers with the same solid set of standard benchmarks that they have for Ethernet today—making it more likely that they will accept wireless connectivity for their enterprise networks.

**Figure 2.** RF cables connect to the 50-V antenna ports of the devices-under-test with antennas removed. Programmable RF attenuator settings emulate physical distances between devices.

The 802.11T committee plans to model its work after the IETF Requests for Comment (RFCs) 2285, 2544, and 2889 (Ref. 2), specifying metrics and methods for evaluating the performance of Ethernet switches. The author of two of these RFCs, Bob Mandeville of Iometrix, is actively working with the committee. Measurements such as throughput, packet loss, delay, and jitter can be based on the RFCs, but 802.11T will have to define new wireless-specific metrics.

**Table 1** summarizes the wireless test metrics (such as packet forwarding rate, jitter, and rate vs. range) and the numerous test configurations (ranging from number of clients to physical layer rate selection) for each metric currently being studied by 802.11T. Adding mobility and interference considerations to this list will compound the difficulty of the group's task.

Active participants in the 802.11T committee include representatives of more than 16 companies, including Broadcom, Intel, Microsoft, Symbol, Texas Instruments, and the University of New Hampshire Interoperability Lab. The last face-to-face meeting of the 802.11T committee was September 12 in Berlin, Germany; the next will be held November 14–19 in San Antonio, TX.

The group also holds weekly teleconference sessions. Those wishing to join the teleconferences should send an e-mail request to Charles Wright, 802.11T committee chair and Azimuth Systems chief scientist:

[charles\\_wright@azimuth.net](mailto:charles_wright@azimuth.net).

---

### Author Information

**Fanny Mlinarsky** is the founder and CTO of Azimuth Systems. During her 20-year career, she has held engineering and management positions at various companies. A frequent presenter at industry conferences and an active participant in the development of networking standards at IEEE, ISO/IEC, and TIA, she holds a BS in electrical engineering and a BA in

computer science from Columbia University.

## REFERENCES

1. IEEE 802.11, "Wireless Local Area Networks—The Working Group for WLAN Standards." [grouper.ieee.org/groups/802/11](http://grouper.ieee.org/groups/802/11).
2. Mandeville, R, "Benchmarking Terminology for LAN Switching Devices," RFC 2285, February 1998. [www.ietf.org/rfc/rfc2285.txt](http://www.ietf.org/rfc/rfc2285.txt).

•

[Free print subscription](#)



[Print-friendly version](#)



[Email this story to a friend](#)



**FROM THE EDN Network**

**Samsung Ships Blu-ray DVD to U.S.** *Electronic News*, 6/15/2006

**Anritsu runs RF gamut with IMS debuts** *Test & Measurement World*, 6/14/2006 8:58:00 AM

**China Applies for World Semiconductor Council Membership** *Electronic News*, 6/14/2006

**Merrill Lynch report cites rising inventory** *Electronic Business*, 6/6/2006

Sponsored by:

**EB STORY BEHIND THE STORY**

## MORE ARTICLES

[UL sets up Singapore office](#)

06/05/2006, Test & Measurement World

[Azimuth provides platform for 802.11n functional testing](#)

06/01/2006, Test & Measurement World

[ADS and Genesys RF tools get design links](#)

05/30/2006, Test & Measurement World

[Network Processing Forum to merge with Optical Internetworking Forum](#)

05/06/2006, Test & Measurement World

## Ads By Google

### [Protect Your Wireless LAN](#)

Detect Rogues, Mitigate Attacks Check Traffic Signal & Interference  
[www.wifimanager.com](http://www.wifimanager.com)

### [EasySync Ethernet-Serial](#)

One to 8 Port Ethernet Serial RS232/422/485 Servers from £85  
[www.easysync.co.uk](http://www.easysync.co.uk)

[Editorial Staff Contacts](#) | [Sales Staff Contacts](#) | [Free Subscriptions](#)

© 2006 [Reed Business Information](#), a division of [Reed Elsevier Inc.](#) All rights reserved.  
Use of this web site is subject to its [Terms and Conditions of Use](#). View our [Privacy Policy](#)

Test & Measurement World, 225 Wyman Street, Waltham, MA 02451, USA  
Phone: 781-734-8423 Fax: 781-734-8070 E-mail: [tmw@reedbusiness.com](mailto:tmw@reedbusiness.com)