

# ***Dynamon SR***

Model EPD

**“Concrete admixtures - Plasticisers  
and Superplasticisers”**

(Declaration number EPD-EFC-20150091-IA G1-EN)



## DECLARATION OF CONFORMITY FOR PRODUCTS WITH MODEL EPDS

The European Federation of Concrete Admixtures Associations (EFCA) has developed Model Environmental Product Declarations (Model EPD) for six categories of admixtures. These model EPDs have been verified as being in compliance with EN 15804 and ISO 14025 and published by the independent Institute for Construction and Environment in Germany (IBU). The Model EPD are also available for download from the EFCA website. Mapei S.p.A. is a member of ASSIAD (Associazione Italiana Produttori Additivi e Prodotti per Calcestruzzo) which is a national association member of EFCA. This gives the company the right to declare that a specific EFCA Model EPD applies to the named product listed below, by using an IBU-approved guideline procedure, to confirm that any particular product is within the scope of a specific product category Model EPD. This means that the life cycle assessment data and other content of the Model EPD apply to this named products and may be used for sustainability assessment of the construction products and construction projects, in which it is used.

Mapei declares that the products

***Dynamon SR 51, Dynamon SR 52, Dynamon SR 54, Dynamon SR 542,  
Dynamon SR 912, Dynamon SR 913, Dynamon SR 914,  
Dynamon SR 915, Dynamon SR 916, Dynamon SR1, Dynamon SR2,  
Dynamon SR21, Dynamon SR31 and Dynamon SR4***

meet the criteria of the attached Model EPD  
**“Concrete admixtures - Plasticisers and Superplasticisers”**  
(Declaration number EPD-EFC-20150091-IAG1-EN)

For any enquiries please contact us at [sustainability@mapei.it](mailto:sustainability@mapei.it)

Mapei S.p.A.

Giorgio Squinzi  
Amministratore Unico



# ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804

Owner of the Declaration	European Federation of Concrete Admixtures Associations Ltd. (EFCA)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-EFC-20150091-IAG1-EN
ECO EPD Ref. No.	ECO-00000385
Issue date	14/09/2015
Valid to	13/09/2020

## Concrete admixtures – Plasticisers and Superplasticisers European Federation of Concrete Admixtures Associations Ltd. (EFCA)

[www.ibu-epd.com](http://www.ibu-epd.com) / <https://epd-online.com>





## 1. General Information

### European Federation of Concrete Admixtures Associations Ltd. (EFCA)

#### Programme holder

IBU - Institut Bauen und Umwelt e.V.  
Panoramastr. 1  
10178 Berlin  
Germany

#### Declaration number

EPD-EFC-20150091-1AG1-EN

#### This Declaration is based on the Product Category Rules:

Concrete admixtures, 07.2014  
(PCR tested and approved by the SVR)

#### Issue date

14/09/2015

#### Valid to

13/09/2020



Prof. Dr.-Ing. Horst J. Bossenmayer  
(President of Institut Bauen und Umwelt e.V.)



Dr. Burkhard Lehmann  
(Managing Director IBU)

### Concrete admixtures – plasticisers and superplasticisers

#### Owner of the Declaration

European Federation of Concrete Admixtures Associations Ltd. (EFCA)  
Radius House, 51 Clarendon Road, Watford,  
Herts, WD17 1HP United Kingdom

#### Declared product / Declared unit

1 kg of plasticisers and superplasticisers, density: 1 - 1.6 kg/l

#### Scope:

This validated Declaration entitles EFCA to bear the symbol of the Institut Bauen und Umwelt e.V. It exclusively applies for the product groups referred to for plants operated in Belgium, France, Germany, Italy, Netherlands, Norway, Spain, Sweden, Switzerland, Turkey and the United Kingdom by companies that are members of EFCA National Associations in these countries and for a period of five years from the date of issue. It involves a Model EPD where the product displaying the highest environmental impact in a group was selected for calculating the Life Cycle Assessment. Please refer to the EFCA website [www.efca.info](http://www.efca.info) for a list of National Associations.


The application of this EPD is only possible for member companies of EFCA's member associations and only for specific formulations with a total score below the declared maximum score for a product group according to the associated guidance document. The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

#### Verification

The CEN Norm /EN 15804/ serves as the core PCR

Independent verification of the declaration according to /ISO 14025/

☐ internally ☒ externally



Matthias Schulz  
(Independent verifier appointed by SVR)

## 2. Product

### 2.1 Product description

Admixtures are liquid or powdery agents that are introduced in small amounts (< 5% by mass of the cement content) to concrete while it is being mixed and that enhance the properties of the fresh and/or hardened concrete.

Plasticisers and superplasticisers are admixtures which reduce the water content of mixed concrete without detriment to its consistency or enhance its slump with or without change to the water content or cause both effects simultaneously. They can also display a retarding effect when used as combination products.

The results of the Life Cycle Assessment provided in this declaration have been selected from the product

with the highest environmental impact (worst-case scenario).

### 2.2 Application

Concrete admixtures are used as constituent materials for the production of concrete, mortar and grout (unreinforced concrete, reinforced and prestressed concrete, site-mixed and ready-mixed concrete, precast concrete). Their application should be in line with the manufacturer's technical documents and Declaration of Performance.

### 2.3 Technical Data

Plasticisers and superplasticisers must comply with the general requirements of /EN 934-1:2008/ and the additional requirements of /EN 934-2:2009+A1:2012/.

The corresponding requirements in line with /EN 934-1:2008/ and /EN 934-2:2009+A1:2012/ must be maintained.

#### Constructional data

Name	Value	Unit
Density /ISO 758/	1 - 1.6	g/ml
Solids content /EN 480-8/	- <sup>1</sup>	M.-%
pH value /ISO 4316/	- <sup>1</sup>	- $\log_{10}(a_{H^+})$
Chloride content /EN 480-10/	Maximum value to be declared by the manufacturer	M.-%
Alkali content /EN 480-12/	Maximum value to be declared by the manufacturer	M.-%
Corrosion behavior /EN 934-1/, /EN 480-14/	- <sup>2</sup>	$\mu A/cm^2$
SiO <sub>2</sub> content /EN 192-2/	- <sup>3</sup>	M.-%
Air content of fresh concrete /EN 12350-7/	Test mix $\leq 2\%$ by volume above control mix unless stated otherwise by the manufacturer	Vol.-%
Compressive strength /EN 12390-3/	-□	N/mm <sup>2</sup>
Water reduction /EN 12350-2/, /EN 12350-5/ Plasticiser	Test mix $\geq 5\%$ compared to control mix Superplasticiser: Test mix $\geq 12\%$ compared to control mix	mm
Increasing / maintaining of consistence /EN 12350-2/, /EN 12350-5/ Superplasticiser	-□	mm
Setting time /EN 480-2/ Accelerator/Retarder	-□	min
Air void Characteristics in hardened concrete /EN 480-11/ Air entrainer	-□	mm
Capillary water absorption /EN 480-5/ Densifier	-□	g/mm <sup>2</sup>

<sup>1</sup> Value will be made available to user on request

<sup>2</sup> No corrosion behaviour test is required for admixtures which only contain active substances in the list of approved substances to /EN 934-1/, Annex A.1 and in the list of declared substances to /EN 934-1/, Annex A.2.

<sup>3</sup> Maximum value must only be indicated when SiO<sub>2</sub> percentage by mass > 5%

□ Details not relevant for this type of admixture

□ Concrete plasticiser:

At 7 and 28 days: Test mix  $\geq 110\%$  of control mix  
Superplasticiser (tested at equal consistence):

At 1 day:

Test mix  $\geq 140\%$  of control mix

At 28 days:

Test mix  $\geq 115\%$  of control mix

Superplasticiser (tested at equal w/c ratio): At 28 days:

Test mix  $\geq 90\%$  of control mix

□ Increase in consistence

Increase in slump  $\geq 120$  mm from initial ( $30 \pm 10$ ) mm  
or

Increase in flow  $\geq 160$  mm from initial ( $350 \pm 20$ ) mm

Retention of consistence 30 min after the addition:

the consistence of test mix  $\geq$  initial consistence of the control mix

#### 2.4 Application rules

For products placed on the market in the European Economic Area (EEA) the Construction Product Regulation (Regulation (EU) No 305/2011) applies /CPR/. Outside of the EEA, the corresponding national regulation applies. Admixture products placed on the market under the CPR require a Declaration of Performance and CE marking taking consideration of /EN 934-2:2009+A1:2012/.

For the application and use of the products the respective national provisions apply.

#### 2.5 Delivery status

Plasticisers and superplasticisers are usually supplied in liquid, paste or powder form in containers made of steel or plastic.

Typical container sizes are canisters containing approx. 25 kg, drums with approx. 200 kg or Intermediate Bulk Containers (IBC) with 1000 kg. The containers are shipped on wooden pallets.

For larger applications, loose deliveries in tank trucks with a capacity in excess of 1 tonne are also used.

#### 2.6 Base materials / Ancillary materials

Plasticisers and superplasticisers essentially contain either lignosulphonate, naphthalene sulphonate, melamine sulphonate and polycarboxylate/polycarboxylic or mixtures thereof. Defoaming agents and preservatives are added as minor components and auxiliaries.

Active substance concentration lies between 10 and 40% by mass. The typical dosage of plasticisers lies between 0.2 and 0.5% by mass in relation to the cement weight. The typical dosage of superplasticisers lies between 0.4 and 2.0% by mass in relation to the cement weight.

The products covered by this EPD typically contain the following proportions by mass of constituent materials and auxiliaries referred to:

Lignosulphonate*:	max. 35%
Naphthalene sulphonate*:	max. 30%
Melamine sulphonate*:	max. 45%
Polycarboxylate*:	max. 35%
Additives:	max. 5%
Water:	approx. 55 - 75%

##### \*Solid content

These volumes are average values and the composition of products complying with the EPD can deviate from these concentration levels in individual cases.

*Note: For companies to declare their products within the scope of this EPD it is not sufficient to simply comply with the product composition shown above.*

*The application of this EPD is only possible for member companies of EFCA's member associations and only for specific formulations with a total score below the declared maximum score for a product group according to the associated guidance document.*

Small volumes (< 0.5% by mass) of biocides with functional chemical groups for example isothiazolinones or dioxahexane are used as preservatives in concrete admixtures during storage. More detailed information is available in the respective manufacturer's documentation (e.g. product data sheets, safety data sheets).

Unless indicated on the safety data sheet, concrete admixtures do not contain any substances in concentrations of more than 0.1% which are included in the list of Substances of Very High Concern (SVHC) for inclusion in Annex XIV of the REACH regulation.



No flame retardants are used in concrete admixtures.

## **2.7 Manufacture**

Concrete admixtures are usually manufactured by mixing ingredients together in batch mode and filling containers for dispatch. The process follows quality standards outlined in /EN 934-6:2001+A1:2005/.

## **2.8 Environment and health during manufacturing**

As a general rule, no environmental or health protection measures other than those specified by law are necessary.

## **2.9 Product processing/Installation**

During concrete manufacture, concrete admixtures are usually added along with the mixing water or included in premixed concrete.

Health and safety measures (eye protection, hand protection, possibly respiratory equipment and body protection) are to be taken and consistently adhered to in accordance with the information on the safety data sheet and conditions on site.

## **2.10 Packaging**

Reusable containers are, where practicable taken back by the manufacturer and redirected into the production circuit. Empty plastic or steel containers which can no longer be used are recyclable.

Wooden reusable pallets are, where practicable taken back by the manufacturer or building material trader who returns them to the building product manufacturer redirecting them into the production process.

## **2.11 Condition of use**

During the use phase, concrete admixtures are firmly bound into the cement matrix in hardened concrete. Concrete admixtures make an essential contribution towards optimising the physical and chemical properties of concrete enhancing its performance, durability, economic value and sustainability.

## **2.12 Environment and health during use**

During the use phase, concrete admixtures are firmly bound into the cement matrix in hardened concrete. No relevant risks are known for water, air and soil if the products are used as designated.

## **2.13 Reference service life**

Not relevant as this declaration relates to a preliminary product.

## **2.14 Extraordinary effects**

### **Fire**

Not relevant as this declaration relates to a preliminary product.

### **Water**

Not relevant as this declaration relates to a preliminary product.

### **Mechanical destruction**

Not relevant as this declaration relates to a preliminary product.

## **2.15 Re-use phase**

Not relevant as this declaration relates to a preliminary product.

## **2.16 Disposal**

Empty, dried containers are directed to the recycling process where practicable. Residue must be directed to proper waste disposal taking consideration of local guidelines.

## **2.17 Further information**

More information is available in the manufacturers' product or safety data sheets on the manufacturers' Web sites or on request.

An electronic version of this declaration is available at [www.efca.info](http://www.efca.info) and [www.bau-umwelt.com](http://www.bau-umwelt.com)

# **3. LCA: Calculation rules**

## **3.1 Declared Unit**

This EPD refers to the declared unit of 1 kg concrete admixture with a density of 1-1.6 kg/l in accordance with the IBU PCR 07.2014 Part B for concrete admixtures. The results of the Life Cycle Assessment provided in this declaration have been selected from the product with the highest environmental impact (worst-case scenario).

Depending on the application, a corresponding conversion factor such as the density to convert volumetric use to mass must be taken into consideration.

## **3.2 System boundary**

Modules A1, A2 and A3 are taken into consideration in the LCA:

- A1 Production of preliminary products
- A2 Transport to the plant
- A3 Production incl. provision of energy, production of packaging as well as auxiliaries and consumables and waste treatment

The Declaration is therefore "cradle-to-gate".

## **3.3 Estimates and assumptions**

For this EPD formulation and production data defined by EFCA were considered. Production waste was assumed to be disposed of to landfill without credits as a worst case.

An average of plastic containers and wooden pallets was considered in the LCA.

## **3.4 Cut-off criteria**

All raw materials submitted for the formulations and production data were taken into consideration. The manufacture of machinery, plant and other infrastructure required for production of the products under review was not taken into consideration in the LCA.

Transport of packaging materials is also excluded.

## **3.5 Background data**

Data from the GaBi 6 data base was used as background data.

## **3.6 Data quality**

Representative products were applied for this EPD and the product in the group displaying the highest environmental impact was selected for calculating the



LCA results. The data sets are no more than 4 years old.

Production data and packaging are based on details provided by the manufacturer. The formulation used for evaluation refers to a specific product.

The data quality of the background data is considered to be good.

### **3.7 Period under review**

Representative formulations were compiled by EFCA in 2011.

### **3.8 Allocation**

No allocations were applied for production.

### **3.9 Comparability**

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to /EN 15804/ and the building context, respectively the product-specific characteristics of performance, are taken into account.

## **4. LCA: Scenarios and additional technical information**

In accordance with the IBU PCR 07.2014 Part A, no scenarios are indicated as only Modules A1-A3 are declared.

## 5. LCA: Results

### DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE NOT DECLARED)

PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND

### RESULTS OF THE LCA - ENVIRONMENTAL IMPACT: 1 kg plasticisers and superplasticisers

Parameter	Unit	A1-A3
Global warming potential	[kg CO <sub>2</sub> -Eq.]	1.88E+0
Depletion potential of the stratospheric ozone layer	[kg CFC11-Eq.]	2.30E-10
Acidification potential of land and water	[kg SO <sub>2</sub> -Eq.]	2.92E-3
Eutrophication potential	[kg (PO <sub>4</sub> ) <sup>3</sup> -Eq.]	1.03E-3
Formation potential of tropospheric ozone photochemical oxidants	[kg ethene-Eq.]	3.12E-4
Abiotic depletion potential for non-fossil resources	[kg Sb-Eq.]	1.10E-6
Abiotic depletion potential for fossil resources	[MJ]	2.91E+1

### RESULTS OF THE LCA - RESOURCE USE: 1 kg plasticisers and superplasticisers

Parameter	Unit	A1-A3
Renewable primary energy as energy carrier	[MJ]	1.51E+0
Renewable primary energy resources as material utilization	[MJ]	0.00
Total use of renewable primary energy resources	[MJ]	1.51E+0
Non-renewable primary energy as energy carrier	[MJ]	2.66E+1
Non-renewable primary energy as material utilization	[MJ]	4.82E+0
Total use of non-renewable primary energy resources	[MJ]	3.14E+1
Use of secondary material	[kg]	0.00
Use of renewable secondary fuels	[MJ]	0.00
Use of non-renewable secondary fuels	[MJ]	0.00
Use of net fresh water	[m <sup>3</sup> ]	6.04E-3

### RESULTS OF THE LCA – OUTPUT FLOWS AND WASTE CATEGORIES:

#### 1 kg plasticisers and superplasticisers

Parameter	Unit	A1-A3
Hazardous waste disposed	[kg]	5.17E-6
Non-hazardous waste disposed	[kg]	2.56E-2
Radioactive waste disposed	[kg]	9.00E-4
Components for re-use	[kg]	0.00
Materials for recycling	[kg]	0.00
Materials for energy recovery	[kg]	0.00
Exported electrical energy	[MJ]	0.00
Exported thermal energy	[MJ]	0.00

## 6. LCA: Interpretation

When considering upstream production and transport of pre-products as well as manufacturing of the concrete admixture (modules A1-A3), the main driver of impacts in all categories is production of pre-products (module A1).

In the categories of ozone depletion potential (ODP), renewable primary energy demand (PERT), radioactive waste, and acidification potential (AP) a fairly important contributor is the European electricity grid mix, which also has minor influence on photochemical ozone creation potential (POCP).

The plastic packaging of the concrete admixture also makes a minor contribution, especially to abiotic depletion potential for fossil resources (ADPF), photochemical ozone creation potential (POCP), and

non-renewable primary energy demand (PENRT), as do wooden pallets (in the case of PERT).

Generally, treatment of production waste has negligible influence on results in all impact categories for this product type.



## 7. Requisite evidence

As this involves a declaration of preliminary products, special tests and evidence within the framework of drawing up this Model Environmental Product Declaration have not been carried out or provided.

## 8. References

### Institut Bauen und Umwelt

Institut Bauen und Umwelt e.V., Berlin(pub.):  
Generation of Environmental Product Declarations (EPDs);  
[www.ibu-epd.de](http://www.ibu-epd.de)

### ISO 14025

DIN EN ISO 14025:2011-10: Environmental labels and declarations — Type III environmental declarations — Principles and procedures

### EN 15804

EN 15804:2012-04+A1 2013: Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products

### CPR

Construction Production Regulation (EU) No 305/2011 of the European parliament and of the council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC

### EN ISO 9001:2008

Quality management systems – Requirements (ISO 9001:2008)

### GaBi 6 software & documentation

Data base for Life Cycle Engineering LBP, University of Stuttgart and thinkstep AG, documentation of GaBi 6 data sets <http://documentation.gabi-software.com/>, 2014

### EN 196-2:2013

Test methods for cement – Part 2: Chemical analysis of cement

### EN 206:2013

Concrete – Part 1: Specification, performance, production and conformity

### EN 480-1:2014

Admixtures for concrete, mortar and grout – Test methods – Part 1: Reference concrete and reference mortar for testing

### EN 480-2:2006

Admixtures for concrete, mortar and grout – Test methods – Part 2: Determination of setting time

### EN 480-4:2005

Admixtures for concrete, mortar and grout – Test methods – Part 4: Determination of bleeding of concrete

### EN 480-5:2005

Admixtures for concrete, mortar and grout – Test methods – Part 5: Determination of capillary absorption

### EN 480-6:2005

Admixtures for concrete, mortar and grout – Test methods – Part 6: Infra red analysis

### EN 480-8:2012

Admixtures for concrete, mortar and grout – Test methods – Part 8: Determination of the conventional dry material content

### EN 480-10:2009

Admixtures for concrete, mortar and grout – Test methods – Part 10: Determination of water-soluble chloride content

### EN 480-11:2005

Admixtures for concrete, mortar and grout – Test methods - Part 11: Determination of air void characteristics in hardened concrete

### EN 480-12:2005

Admixtures for concrete, mortar and grout – Test methods – Part 12: Determination of the alkali content of admixtures

### EN 480-14:2006

Admixtures for concrete, mortar and grout – Test methods – Part 14: Determination of the effect on corrosion susceptibility of reinforcing steel by potentiostatic electro-chemical test

### EN 934-1:2008

Admixtures for concrete, mortar and grout – Part 1: Common aspects

### EN 934-2:2009+A1:2012

Admixtures for concrete, mortar and grout – Part 2: Concrete admixtures – Definitions, requirements, conformity, marking and labelling

### EN 934-5:2007

Admixtures for concrete, mortar and grout – Part 5: Admixtures for sprayed concrete – Definitions, requirements, conformity, marking and labelling

### EN 934-6:2001+A1:2005

Admixtures for concrete, mortar and grout – Part 6: Sampling, conformity control and evaluation of conformity

### EN 12350-2:2009

Testing fresh concrete – Part 2: Slump test

### EN 12390-3:2009

Testing hardened concrete – Part 3: Compressive strength of test specimens

**EN 12350-5:2009**

Testing fresh concrete – Part 5: Flow table test

**EN 12350-7:2009**

Testing fresh concrete – Part 7: Air content – Pressure methods

**EN 14487-1:2005**

Sprayed concrete – Part 1: Definitions, specifications and conformity

**EWC/AVV waste code**

Directive governing introduction of the European Waste Catalogue  
<http://www.ngs-mbh.de/zs/eak.html>

**ISO 758:1976**

Liquid chemical products for industrial purposes;  
Determination of density at 20 °C

**ISO 4316:1977**

Surface active agents; Determination of the pH value of aqueous solutions; Potentiometric method

**PCR Part A**

Product Category Rules for Building-Related Products and Services, Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project report, Version 1.2, Institut Bauen und Umwelt e.V., 2013-04

**PCR Part B**

Product Category Rules for Construction Products, Part B: Requirements on the EPD for concrete admixtures, 2014-07

**REACH Directive**

European Parliament and Council: Directive on registering, evaluating, approving and restricting chemical substances, 2006-12

**Publisher**

Institut Bauen und Umwelt e.V.  
Panoramastr. 1  
10178 Berlin  
Germany

Tel +49 (0)30 3087748- 0  
Fax +49 (0)30 3087748- 29  
Mail [info@ibu-epd.com](mailto:info@ibu-epd.com)  
Web [www.ibu-epd.com](http://www.ibu-epd.com)

**Programme holder**

Institut Bauen und Umwelt e.V.  
Panoramastr. 1  
10178 Berlin  
Germany

Tel +49 (0)30 - 3087748- 0  
Fax +49 (0)30 - 3087748 - 29  
Mail [info@ibu-epd.com](mailto:info@ibu-epd.com)  
Web [www.ibu-epd.com](http://www.ibu-epd.com)



thinkstep

**Author of the Life Cycle Assessment**

thinkstep AG  
Hauptstr. 111 - 113  
70771 Leinfelden-Echterdingen  
Germany

Tel +49 (0)711-341817-0  
Fax +49 (0)711-341817-25  
Mail [info@thinkstep.com](mailto:info@thinkstep.com)  
Web [www.thinkstep.com](http://www.thinkstep.com)

**Owner of the Declaration**

European Federation of Concrete  
Admixtures Associations Ltd. (EFCA)  
Radius House, Clarendon Road 51  
WD17 1HP Watford, Herts  
United Kingdom

Tel -  
Fax -  
Mail [secretary@efca.info](mailto:secretary@efca.info)  
Web [www.efca.info](http://www.efca.info)