

Reach Bravo Kinematics and Dynamics

Blueprint Lab

August 2020

1 Kinematics

Link	d (mm)	θ	a (mm)	α
0	107.4	$\theta_0 + \pi$	46.0	$\pi/2$
1	0.0	$\theta_1 - \pi/2 + \theta_a$	293.6	0.0
2	0.0	$\theta_2 - \pi/2 - \theta_a$	40.8	$-\pi/2$
3	-160.0	θ_3	40.8	$-\pi/2$
4	0.0	θ_4	40.8	$-\pi/2$
5	-223.5	θ_5	0.0	$\pi/2$
6	0.0	$-\pi/2$	120.0	0.0

Table 1: Standard DH Parameters for Bravo 7 where $\theta_a = \tan^{-1}\left(\frac{5.2}{293.55}\right)$




Figure 1: Bravo 7 joint frames (x,y,z)

2 Inertial Properties

Link	Mass (<i>kg</i>)	COM (<i>mm</i>)	I (<i>kg.mm²</i>)
0	1.25	(-18 -4 -1)	$\begin{pmatrix} 2108 & 182 & -15 \\ 182 & 2573 & -21 \\ -15 & -21 & 3483 \end{pmatrix}$
1	1.55	(17 -7 57)	$\begin{pmatrix} 11442 & -484 & 3405 \\ -484 & 12980 & -1265 \\ 3405 & -1265 & 3202 \end{pmatrix}$
2	1.98	(117 15 6)	$\begin{pmatrix} 3960 & 4200 & 3204 \\ 4200 & 69099 & -24 \\ 3204 & -24 & 70450 \end{pmatrix}$
3	1.14	(22 -29 1)	$\begin{pmatrix} 3213 & -1548 & -31 \\ -1548 & 2327 & 6 \\ -31 & 6 & 4340 \end{pmatrix}$
4	1.14	(18 6 -117)	$\begin{pmatrix} 21232 & 330 & -3738 \\ 330 & 22252 & -1278 \\ -3738 & -1278 & 2054 \end{pmatrix}$
5	1.03	(20 -24 1)	$\begin{pmatrix} 2430 & -1144 & -40 \\ -1144 & 2026 & 11 \\ -40 & 11 & 3330 \end{pmatrix}$
6	1.04	(0 0 -128)	$\begin{pmatrix} 22359 & 1 & -19 \\ 1 & 22363 & 15 \\ -19 & 15 & 936 \end{pmatrix}$
7	0.47	(28 -1 0)	$\begin{pmatrix} 244 & -12 & 0 \\ -12 & 1130 & 1 \\ 0 & 1 & 1178 \end{pmatrix}$

Table 2: Inertial properties for Bravo 7 (Link 7 is for interlocking jaws in the closed position)




Figure 2: Inertial frames for Bravo 7

3 Hydrodynamic Properties

3.1 Buoyancy

Link	Volume (L)	COB (mm)
0	0.72	$(-18 \ -3 \ -3)$
1	0.60	$(27 \ -11 \ 92)$
2	1.94	$(145 \ 35 \ -1)$
3	0.47	$(33 \ -43 \ -7)$
4	0.51	$(20 \ 12 \ -140)$
5	0.43	$(33 \ -38 \ -8)$
6	0.48	$(0 \ 0 \ -152)$
7	0.16	$(28 \ 1 \ 0)$

Table 3: Buoyancy terms with Centre of Buoyancy (COB)