

Implementing Asynchronous Multi-Party Computation


Martin Geisler

BRICS
Department of Computer Science
University of Aarhus

February 21st, 2008

Part I

Secure Integer Comparison



Secure Integer Comparison

- ▶ Given integers a and b , securely compute $a > b$.

Secure Integer Comparison


- ▶ Given integers a and b , securely compute $a > b$.
- ▶ Many variations:
 - ▶ a , b can be private, public or secret shared.
 - ▶ Same for the result.
 - ▶ We can have two or more players.

Auctions

- ▶ Traditional auction:
 - ▶ Bidders must be on-line.
 - ▶ Bidding continues until a deadline is reached.

Auctions


- ▶ Traditional auction:
 - ▶ Bidders must be on-line.
 - ▶ Bidding continues until a deadline is reached.
- ▶ Maximum bid auction:



- ▶ P_i may submit a maximum bid M_i .

Auctions


- ▶ Traditional auction:
 - ▶ Bidders must be on-line.
 - ▶ Bidding continues until a deadline is reached.
- ▶ Maximum bid auction:



- ▶ P_i may submit a maximum bid M_i .
- ▶ A public current price x is incremented until only one $M_i > x$.

Auctions

- ▶ Traditional auction:
 - ▶ Bidders must be on-line.
 - ▶ Bidding continues until a deadline is reached.
- ▶ Maximum bid auction:



- ▶ P_i may submit a maximum bid M_i .
- ▶ A public current price x is incremented until only one $M_i > x$.

Auctions


- ▶ Traditional auction:
 - ▶ Bidders must be on-line.
 - ▶ Bidding continues until a deadline is reached.
- ▶ Maximum bid auction:



- ▶ P_i may submit a maximum bid M_i .
- ▶ A public current price x is incremented until only one $M_i > x$.

Auctions


- ▶ Traditional auction:
 - ▶ Bidders must be on-line.
 - ▶ Bidding continues until a deadline is reached.
- ▶ Maximum bid auction:



- ▶ P_i may submit a maximum bid M_i .
- ▶ A public current price x is incremented until only one $M_i > x$.

Auctions


- ▶ Traditional auction:
 - ▶ Bidders must be on-line.
 - ▶ Bidding continues until a deadline is reached.
- ▶ Maximum bid auction:



- ▶ P_i may submit a maximum bid M_i .
- ▶ A public current price x is incremented until only one $M_i > x$.


Auctions

- ▶ Traditional auction:
 - ▶ Bidders must be on-line.
 - ▶ Bidding continues until a deadline is reached.
- ▶ Maximum bid auction:



- ▶ P_i may submit a maximum bid M_i .
- ▶ A public current price x is incremented until only one $M_i > x$.
- ▶ Problem: Auction house knows M_i and is a trusted third party.

Removing Trust in the Auction House



- Want to remove trusted party T .

Removing Trust in the Auction House


A

B

- ▶ Want to remove trusted party T .
- ▶ Split T into parties A and B .

P_i

Removing Trust in the Auction House



- ▶ Want to remove trusted party T .
- ▶ Split T into parties A and B .
- ▶ User P_i shares M_i into a and b .
- ▶ A gets a , B gets b .
- ▶ A and B run a comparison protocol.

Homomorphic Encryption Scheme

- Encryption:

$$E_{pk}(m, r) = g^m h^r \bmod n.$$

- Homomorphic:

$$E_{pk}(m, r) \cdot E_{pk}(m', r') \bmod n = E_{pk}(m + m' \bmod u, r + r').$$

- Check $c = E_{pk}(m, r)$ for $m = 0$:

$$c^v \bmod n = (g^v)^m \bmod n.$$


Calculating $M > x$

x : $\begin{array}{c} \ell \qquad \qquad \qquad 1 \\ \boxed{1 \mid 0 \mid 1 \mid 0 \mid 1 \mid 1 \mid 0 \mid 1 \mid 0 \mid 0} \end{array}$

M : $\boxed{1 \mid 0 \mid 1 \mid 1 \mid 0 \mid 1 \mid 0 \mid 0 \mid 1 \mid 0}$


- ▶ We wish to compute $M > x$ for ℓ -bit numbers.
- ▶ x_i is the i 'th bit of x , m_i is the i 'th bit of M .

Calculating $M > x$




- ▶ We wish to compute $M > x$ for ℓ -bit numbers.
- ▶ x_i is the i 'th bit of x , m_i is the i 'th bit of M .

Calculating $M > x$




- ▶ We wish to compute $M > x$ for ℓ -bit numbers.
- ▶ x_i is the i 'th bit of x , m_i is the i 'th bit of M .

Calculating $M > x$



- ▶ We wish to compute $M > x$ for ℓ -bit numbers.
- ▶ x_i is the i 'th bit of x , m_i is the i 'th bit of M .


Calculating $M > x$



- ▶ We wish to compute $M > x$ for ℓ -bit numbers.
- ▶ x_i is the i 'th bit of x , m_i is the i 'th bit of M .
- ▶ Define the following:

$$c_i = x_i - m_i + 1 + \sum_{j=i+1}^{\ell} m_j \oplus x_j.$$

Calculating $M > x$




- ▶ We wish to compute $M > x$ for ℓ -bit numbers.
- ▶ x_i is the i 'th bit of x , m_i is the i 'th bit of M .
- ▶ Define the following:

$$c_i = x_i - m_i + 1$$

$$+ \sum_{j=i+1}^{\ell} m_j \oplus x_j.$$


Calculating $M > x$



- ▶ We wish to compute $M > x$ for ℓ -bit numbers.
- ▶ x_i is the i 'th bit of x , m_i is the i 'th bit of M .
- ▶ Define the following:

$$c_i = x_i - m_i + 1 + \sum_{j=i+1}^{\ell} m_j \oplus x_j.$$

Calculating $M > x$




- ▶ We wish to compute $M > x$ for ℓ -bit numbers.
- ▶ x_i is the i 'th bit of x , m_i is the i 'th bit of M .
- ▶ Define the following:

$$c_i = x_i - m_i + 1$$

$$+ \sum_{j=i+1}^{\ell} m_j \oplus x_j.$$

Calculating $M > x$



- ▶ We wish to compute $M > x$ for ℓ -bit numbers.
- ▶ x_i is the i 'th bit of x , m_i is the i 'th bit of M .
- ▶ Define the following:

$$c_i = x_i - m_i + 1$$

$$+ \sum_{j=i+1}^{\ell} m_j \oplus x_j.$$

- ▶ $M > x \iff \exists i : c_i = 0.$

Protocol for $M > x$

A


B

- ▶ A and B know pk , A knows sk .
- ▶ Input x is public, M known to P_i .

P_i

$$M = m_\ell \dots m_1$$

Protocol for $M > x$



$$M = m_\ell \dots m_1$$
$$m_i = a_i + b_i$$

- ▶ A and B know pk , A knows sk .
- ▶ Input x is public, M known to P_i .
- ▶ Input m_i additively secret shared.

Protocol for $M > x$

c_i^A
 A


c_i^B
 B

- ▶ A and B know pk , A knows sk .
- ▶ Input x is public, M known to P_i .
- ▶ Input m_i additively secret shared.
- ▶ A and B compute shares of c_i .

P_i

$$M = m_\ell \dots m_1$$

Protocol for $M > x$




- ▶ A and B know pk , A knows sk .
- ▶ Input x is public, M known to P_i .
- ▶ Input m_i additively secret shared.
- ▶ A and B compute shares of c_i .
- ▶ A sends $E_{pk}(c_i^A)$ to B .

P_i

$$M = m_\ell \dots m_1$$

Protocol for $M > x$



P_i

$$M = m_\ell \dots m_1$$

- ▶ A and B know pk , A knows sk .
- ▶ Input x is public, M known to P_i .
- ▶ Input m_i additively secret shared.
- ▶ A and B compute shares of c_i .
- ▶ A sends $E_{pk}(c_i^A)$ to B.
- ▶ B calculates $E_{pk}(c_i s_i)$ using the homomorphic property.
- ▶ B sends shuffled $E_{pk}(c_i s_i)$ to A.

Protocol for $M > x$

$M > x$

A


B

P_i

$$M = m_\ell \dots m_1$$


- ▶ A and B know pk , A knows sk .
- ▶ Input x is public, M known to P_i .
- ▶ Input m_i additively secret shared.
- ▶ A and B compute shares of c_i .
- ▶ A sends $E_{pk}(c_i^A)$ to B .
- ▶ B calculates $E_{pk}(c_i s_i)$ using the homomorphic property.
- ▶ B sends shuffled $E_{pk}(c_i s_i)$ to A .
- ▶ A checks if any $c_i s_i$ is zero.
- ▶ $\exists i : c_i s_i = 0 \iff M > x$.

Related Work




- ▶ Marc Fischlin's protocol:
- ▶ Blake and Kolesnikov's protocol:

Related Work




- ▶ Marc Fischlin's protocol:
 - ▶ Quadratic residuosity assumption.
 - ▶ Encoding expands by λ factor.
- ▶ Blake and Kolesnikov's protocol:

Related Work




- ▶ Marc Fischlin's protocol:
 - ▶ Quadratic residuosity assumption.
 - ▶ Encoding expands by λ factor.
- ▶ Blake and Kolesnikov's protocol:
 - ▶ Paillier encryption.
 - ▶ No expansion.

Related Work




- ▶ Marc Fischlin's protocol:
 - ▶ Quadratic residuosity assumption.
 - ▶ Encoding expands by λ factor.
- ▶ Blake and Kolesnikov's protocol:
 - ▶ Paillier encryption.
 - ▶ No expansion.
- ▶ Our protocol: Best of both worlds.

Benchmark Results



Part II


Virtual Ideal Functionality Framework



VIFF Overview


- ▶ Framework for specifying MPC.
- ▶ Provides building-blocks for larger protocols.
- ▶ Asynchronous design.
- ▶ Automatic parallel scheduling.

Asynchronous vs. Synchronous




- ▶ All rounds equally fast.
- ▶ Optimal execution.

Asynchronous vs. Synchronous




- ▶ All rounds equally fast.
- ▶ Optimal execution.



- ▶ Processing stalls.
- ▶ Wasted time!

Asynchronous Design


`r = rt.open((x + y) * z)`



- ▶ Entire tree is scheduled at once.
- ▶ Result is a form of “greedy scheduling”.
- ▶ Implicit synchronization, no rounds.

Asynchronous Design

`r = rt.open((x + y) * z)`



- ▶ Entire tree is scheduled at once.
- ▶ Result is a form of “greedy scheduling”.
- ▶ Implicit synchronization, no rounds.
- ▶ Advantages:
 - ▶ Automatic parallel scheduling.
 - ▶ Software scalability.

Example: Hamming Distance

```
def xor(a, b):  
    assert a.field is b.field  
    if a.field is GF256:  
        return a + b  
    else:  
        return a + b - 2 * a * b
```

- ▶ Straight-forward exclusive-or.
- ▶ Fast for $GF(2^8)$ elements.
- ▶ Slower for \mathbb{Z}_p elements.
- ▶ (Already part of VIFF.)


Example: Hamming Distance

```
def xor(a, b):  
    assert a.field is b.field  
    if a.field is GF256:  
        return a + b  
    else:  
        return a + b - 2 * a * b
```

```
def hamming(s, t):  
    distance = 0  
    for i in range(len(s)):  
        distance += xor(s[i], t[i])  
    return distance
```


- ▶ Straight-forward exclusive-or.
 - ▶ Fast for $GF(2^8)$ elements.
 - ▶ Slower for \mathbb{Z}_p elements.
 - ▶ (Already part of VIFF.)
-
- ▶ Hamming distance.
 - ▶ Exclusive-ors run in parallel!

Asynchronous Ideal Functionality



- ▶ Reacts on input from \mathcal{Z} via P_i .
- ▶ Inputs are tagged with a program counter.
- ▶ \mathcal{F} forwards masked input to \mathcal{S} .
- ▶ \mathcal{F} relays traffic between \mathcal{S} and P_i .

Asynchronous Ideal Functionality



- ▶ Reacts on input from \mathcal{Z} via P_i .
- ▶ Inputs are tagged with a program counter.
- ▶ \mathcal{F} forwards masked input to \mathcal{S} .
- ▶ \mathcal{F} relays traffic between \mathcal{S} and P_i .
- ▶ \mathcal{F} queues replies.
- ▶ Released upon signal from \mathcal{S} .

Operations


- ▶ Assignment: $\langle x := v, pc \rangle$.
- ▶ Output: $\langle \text{output}, x, P_i, pc \rangle$.
- ▶ Linear combination: $\langle x := c_1 \cdot x_1 + \dots + c_j \cdot x_j, pc \rangle$.
- ▶ Multiplication: $\langle x := y \cdot z, pc \rangle$.
- ▶ Synchronization: $\langle \text{synchronize}, pc \rangle$.

Operations


- ▶ Assignment: $\langle x := v, pc \rangle$.
- ▶ Output: $\langle \text{output}, x, P_i, pc \rangle$.
- ▶ Linear combination: $\langle x := c_1 \cdot x_1 + \dots + c_j \cdot x_j, pc \rangle$.
- ▶ Multiplication: $\langle x := y \cdot z, pc \rangle$.
- ▶ Synchronization: $\langle \text{synchronize}, pc \rangle$.
- ▶ Direct correspondence to methods in VIFF Runtime.

Simulating Assignment

Real World:




Ideal World:




Simulating Assignment

Real World:




Ideal World:




Simulating Assignment

Real World:




Ideal World:




Simulating Assignment

Real World:




Ideal World:




Simulating Assignment

Real World:




Ideal World:




Simulating Assignment

Real World:




Ideal World:




Simulating Assignment

Real World:




Ideal World:




Simulating Assignment

Real World:




Ideal World:




Simulating Assignment

Real World:




Ideal World:




Simulating Assignment

Real World:




Ideal World:




Simulating Assignment

Real World:



Ideal World:



Performance Results


- ▶ Tested on 3 machines: USA, Norway, and Denmark.

Performance Results

- ▶ Tested on 3 machines: USA, Norway, and Denmark.
- ▶ Tested multiplications and comparisons.


Performance Results

- ▶ Tested on 3 machines: USA, Norway, and Denmark.
- ▶ Tested multiplications and comparisons.
- ▶ Tested parallel and serial multiplications:




Performance Results

- ▶ Tested on 3 machines: USA, Norway, and Denmark.
- ▶ Tested multiplications and comparisons.
- ▶ Tested parallel and serial multiplications:




Performance Results

- ▶ Tested on 3 machines: USA, Norway, and Denmark.
- ▶ Tested multiplications and comparisons.
- ▶ Tested parallel and serial multiplications:




Performance Results


- ▶ Tested on 3 machines: USA, Norway, and Denmark.
- ▶ Tested multiplications and comparisons.
- ▶ Tested parallel and serial multiplications:




Parallel Multiplications



Serial Multiplications



Parallel Comparisons



Future Work

- ▶ Implement protocols for active security.
- ▶ Self-trust: protocols with $t = n - 1$.

Conclusion

Conclusion

- ▶ Comparison protocol for one public and one shared input.
 - ▶ A homomorphic encryption scheme.
 - ▶ Low communication complexity.
 - ▶ Low computational complexity.

Conclusion

- ▶ Comparison protocol for one public and one shared input.
 - ▶ A homomorphic encryption scheme.
 - ▶ Low communication complexity.
 - ▶ Low computational complexity.
- ▶ Virtual Ideal Functionality Framework.
 - ▶ Light-weight design for doing MPC.
 - ▶ Asynchronous design gives automatic parallelism.
 - ▶ See: <http://viff.dk/>.

Conclusion

- ▶ Comparison protocol for one public and one shared input.
 - ▶ A homomorphic encryption scheme.
 - ▶ Low communication complexity.
 - ▶ Low computational complexity.
- ▶ Virtual Ideal Functionality Framework.
 - ▶ Light-weight design for doing MPC.
 - ▶ Asynchronous design gives automatic parallelism.
 - ▶ See: <http://viff.dk/>.

Thank you for listening!